Fo	orm 3160-5 NM CIL CONS. CONTINUED STA Formerly 9-331 awer DEPARTME. I OF TH Artesia, BUREAGOF LAND MA	IE INTER	IOR (Other instruction)	ATE*	Budget Bureau No. 1004-0135 Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO. NM 24867	
	SUNDRY NOTICES AND R (Do not use this form for proposals to drill or to do Use "APPLICATION FOR PERMIT	EPORTS	ON WELLS		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
1.	OIL GAS OTHER		MAY 8 1984		7. UNIT AGREEMENT NAME	
2.	NAME OF OPERATOR		O. C. D.		8. FARM OR LEASE NAME Dog Canyon YF Federal	
3.	Yates Petroleum Corporation ADDRESS OF OPERATOR		ARTESIA, OFFICE		9. WBLL NO.	
	207 South 4th St., Artesia, NM					
3.	See also space 17 below.) At surface			Wildcat & Cesa		
				ľ	11. SBC., T., R., M., OR BLK. AND SURVEY OR ARMA	
	1785 FSL & 1980 FWL, Sec. 15-18S-15E			Unit K, Sec. 15-T18S-R15E		
14	PERMIT NO. 15. BLEVATIONS (S	Show whether D	r, RT, GR, etc.)		12. COUNTY OR PARISH 13. STATE	
	63	372 <b>.4'</b> GR			Otero NM	
16.	Check Appropriate Box To	Check Appropriate Box To Indicate Nature of Notice, Report, or O			ther Data	
	NOTICE OF INTENTION TO:			Berqui	NT REPORT OF:	
	TEST WATER SHUT-OFF PULL OR ALTER CASE	NG	WATER SHUT-OFF		REPAIDING WELL	
	FRANTURE TREAT MULTIPLE COMPLETE	-	FRACTURE TREATMENT	-	ALTEBING CASING	
	SHOOT OR ACIDIZE  REPAIR WELL  CHANGE PLANS		SHOOTING OR ACIDIZING (Other) Perfor	لتتا	ACIDIZO	
	(Other) (Nors: Report results of Completion or Recomple			f multiple completion on Well tion Report and Log form.)		
	TD 8340'. Re-acidized perforations 1538-47' w/1500 gallons 15% NEFE acid, 1% KCL and 15 ball sealers. Swabbed well and recovered fluid. Re-acidized perforations 1538 47' w/5000 gallons 15% NE acid, CO2 and 400# blocking agent. No shows. Set CIBP at 1850' w/30' cement on top. WIH and perforated 1800-08' w/16 .50" holes (2 SPF). Acidized perforations 1800-08' w/1500 gallons NEFE acid, N2 and 14 ball sealers. Swabbed well after acid. No oil or gas. Set CIBP at 1350' w/cement on top. WIH and perforated 1201-10' w/18 .50" holes. Acidized perforations 1201-10' w/1500 gallons 15% NEFE acid, 1% KCL and 17 ball sealers. Swabbed back brackish water. No show of oil or gas.					
	TIGHT HOLE				MAY O 4 1984  Solst. 6 AM.  Men Mayico	
1 -	bereby certify that the foregoing is true and correct				- 113 C 1 113 C 1 1 1 1 1 1 1 1 1 1 1 1 1	
	SIGNED CANTA DO BLITT	TITLE Pro	oduction Supervison	<u>.</u>	DATE 4-30-84	
	APPROVED BY A W	TITLE			DATE	
	CONDITIONS OF APPROVAL, IF ANY:					

\*See Instructions on Reverse Side