

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
JUL 2 1970
 NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

O. C. C.
 Please consider this information confidential

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. L-2899	
7. Unit Agreement Name	
8. Farm or Lease Name Sierra K State	
9. Well No. 1	
10. Field and Pool, or Wildcat Wildcat	
12. County Sierra	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Gulf Oil Corporation
3. Address of Operator Box 670, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER H , 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 12-S RANGE 1-W NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 5112' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

McCormack Drilling Company spudded 17-1/2" surface hole at 11:00 AM, June 24, 1970. Drilled to 545'. Ran 16 joints, 517' of 13-3/8" OD 48# H-40 ST&C casing set and cemented at 533' with 300 sacks of Type #2 neat and 300 sacks of Type No. 2 neat with 2% Ca Cl. Cement circulated. WOC & NU 37 hours. Tested casing with 1000#, 30 minutes, OK.

Started drilling 12-1/4" hole at 545' at 7:30 AM, June 29, 1970

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Orig signed by R.W. Sands TITLE Production Superintendent DATE June 30, 1970

APPROVED BY W.A. Gressett TITLE OIL AND GAS INSPECTOR DATE JUL 2 1970

CONDITIONS OF APPROVAL, IF ANY: