		<i>C</i> /9
	swell, 1-File, 1-Engr. Jim, 1-Foreman HS,	1-BW, 1-JA, 1-Laura Richardson-
RECEIV LOBB	HN OIL CONS. COMMISS Drawer DD	ION Form Approved. Budget Bureau No. 42–R1424
SEP 16 1996	UNITED STATEStesia, NM 88210 DEPARTMENT OF THE INTERIOR	5. LEASE NM-37766
O. C. D.	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUN	DRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME West Elephant Butte Fed
	this form for proposals to drill or to deepen or plug back to a different se Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil well	gas well other	9. WELL NO.
	E OF OPERATOR	1 10. FIELD OR WILDCAT NAME
	Oil Company	Undesignated $w/\rho \rho_{rest}$
P.0.	Box 730, Hobbs, N.M. 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OF
helov	TION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 7, T-12S, R-4W
	URFACE: Unit Ltr. B, 2310' FEL, 990' FNL OP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE Sierra NM
	OTAL DEPTH:	14. API NO.
	CK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, DRT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD 4935' G.L.
TEST WA FRACTUR SHOOT C REPAIR N PULL OR	VELL	NOTE: Report results of multiple completion or zon
CHANGE		011 6 040
ABANDOI (other)	N* 🗍 🎽	CIL & GAS FILTERALD MICHT, SERVICE
<u> </u>		NEW MEXICO
inclu	CRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta ding estimated date of starting any proposed work. If well is o sured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations an
10/24/82	Ran 80 jts of 32 & 24# 3265' of 8 5/8" csg @ 3280', F.C. @ 3235', DV tool @ 14 w/ 660 sacks of lite w/ 1/4# flocele, t Containing 2% CaCl. Plug down @ 9:00 A 2nd stage 672 lite 1/4# flocele tail in CaCl. Plug down @ 4:00 PM. Circ 260 s	A81'. Halliburton cmted 1st stag ail in with 200 sacks of "C". AM. Open DV, Circ 6 hours, 120 s w/ 100 sacks "C" containing 2%
	Received verbal approval to P & A West George Stewart with M.M.S. Roswell Dece	-
12/10/82	Nipple down BOP. 1st plug 6850-7000', 60 sacks of Class "H", 2nd plug 3196-3328', 80 sacks of 2% CaCl tagged @ 3100'. 3rd plug 1331-1531, 30 of class "H".	
12/11/82 Subsurfa	PAA. Nipple down, set 30' plug, 15 sac ice Safety Valve: Manu. and Type	
18 . The	eby certify that the foregoing is true and correct	tendent - December 13, 1982
SIGNED	/D.n. CIOCRECE	tendent December 13, 1982
خرين: معامل	(This space for Federal or State u	APPROVED
CONDITIC	D BY TITLE	
		SEP 1 5 1986