

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	7130'	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	7589'	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	7929'	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	8195'	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison
T. Queen	T. Silurian	647'	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	1020'	T. Mancos	T. McCracken
T. San Andres	T. Simpson	1335'	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee		Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger		T. Dakota	T.
T. Blinebry	T. Gr. Wash		T. Morrison	T.
T. Tubb	T. Granite	4061'	T. Todilto	T.
T. Drinkard	T. Delaware Sand		T. Entrada	T.
T. Abo	T. Bone Springs	4837'	T. Wingate	T.
T. Wolfcamp	T.	5940'	T. Chinle	T.
T. Penn.	T.		T. Permian	T.
T. Cisco (Bunker)	T.	6703'	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	650	650	Anhy, red sh				
650	1020	370	Red sd, sh, anhy				
1020	1350	330	Anhy, sd, sh				
1350	2660	1310	Dolo, anhy				
2660	2960	300	Sd, anhy				
2960	4050	1090	Anhy, sh, dolo, sd				
4050	4270	220	Sd				
4270	4835	565	Anhy, dolo, sh				
4835	5200	365	Red & gr. sh, anhy				
5200	5940	740	Dolo, anhy, sh				
5940	7130	1190	Lm, sh				
7130	7600	470	Sh, lm				
7600	7930	330	Sh, lm, sd				
7930	8200	270	Sh, sd, lm				
8200	8350	150	Lm, sh				