

UNITED STATES
DEPARTMENT OF THE INTERIOR

SUBMIT IN T
(Other instruc
verse side)

Drawer DD

Artesia, NM 88210

Budget Bureau No. 42-R1424

RECEIVED BY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Collier Energy, Inc.

3. ADDRESS OF OPERATOR

P.O. Drawer R Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FSL & 1930' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3880 GL

5. LEASE DESIGNATION AND SERIAL NO.

NM - 16114

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Suzanne Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Double L Queen Assoc.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

3-15S-29E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-22-83 Hole was loaded with mud mixed by Denton Cement.

Used 1 25 sx. cement plug from TD(1891) -1680'.
WOC 2 hours.

Plugged was tagged by Denton Cementing with wireline inside the 4½" casing;
found top at 1680'.

Used 1 50 sx. cement plug, pumped down with Braden-head between 8 5/8" surface
pipe and 4½" casing approximately 310' to surface.

Used 1 25 sx. cement plug from 1120'-1000', inside 4½" casing.

Used 1 25 sx. cement plug from 310', circulated to surface inside 4½" casing.

Set dry hole maker. Removed tank & surface equipment.

Was witnessed by Bob Menendez.

Verbal approval was given by Armondo Lopez on 4-19-83.
And also by James Brasfield on 4-21-83.

Casing was left in hole, pulled 2000' of tubing.

Post ID-2
11-25-83
p+A

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Clerk

DATE April 25, 1983

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
DATE
PETER W. CHESTER

AUG 14 1985

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side

