

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Instructions on reverse side)Form approved by
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-2365	
2. NAME OF OPERATOR Read & Stevens, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -----	
3. ADDRESS OF OPERATOR P.O. Box 2126, Roswell, New Mexico 88201		7. UNIT AGREEMENT NAME -----	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL & 990' FWL Sec. 18, T-15-S, R-28-E, N.M.P.M.		8. FARM OR LEASE NAME Rose	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3610.2' GR-3622' RKB		10. FIELD AND POOL, OR WILDCAT Buffalo Valley Penn. Gas	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18, T-15-S, R-28-E, N.M.P.M.	
		12. COUNTY OR PARISH Chaves	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud and Cement Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well @ 3:00 P.M., 5-11-77. Drilled 17½" hole to 373' RKB. Ran 9 joints 12 3/4", 34#, Foster type, 8 thread casing, total of 375.28', set @ 373' RKB. Cemented w/ 400 sx. Class "C" cement w/ 2% CaCl₂. Circulated 50 sx. cement. Plug down @ 4:40 A.M., 5-12-77. WOC for 18 hrs. Pressure tested casing to 600# for 30 min., held OK. Drilled 11" hole from 373' to 1800'. Ran 44 joints 8 5/8", 24#, S.T.&C. casing, total of 1804.02', set @ 1800' RKB. Cemented w/ 200 sx. Class "H" cement w/ 2% CaCl₂ per sx. Plug down @ 3:15 A.M., 5-15-77. WOC for 18 hrs. Pressure tested casing to 1000# for 30 min. held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 9-28-77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY:

APPROVED

OCT - 1, 1977

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED
SEP 30 1977
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.