

Form 9-331  
May 1963)

OCT 2 1982

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
NM OIL CONS. COMMISSION  
Artesia, NM 88210

Form approved.  
BUDGET BUREAU No. 42-R1424

O.C.D. SUNDY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)		5. LEASE DESIGNATION AND SERIAL NO. NM-2365
OIL GAS WELL <input type="checkbox"/> WELL <input checked="" type="checkbox"/> OTHER _____		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -
NAME OF OPERATOR Read & Stevens, Inc. ✓		7. UNIT AGREEMENT NAME -
ADDRESS OF OPERATOR P.O. Box 1518, Roswell, NM 88201		8. FARM OR LEASE NAME Rose Federal
LOCATION OF WELL (Report location clearly and in accordance with State requirements.* See also space 17 below.) At surface 1315' FNL and 1315' FEL		9. WELL NO. 4
10. FIELD AND POOL, OR WILDCAT Buffalo Valley Penn.		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13-T15S-R27E
12. COUNTY OR PARISH Chaves	13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ABANDON*	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
FRACTURE TREATMENT	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
SHOOTING OR ACIDIZING	<input checked="" type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
(Other)			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-20-82 Perf 8468'-8476', 8', 4 shots/1.

10-21-82 Acidized w/2000gal 7 1/2" Morrowflo w/1000 SCF N<sub>2</sub>/bbl w/25 ballsealers. ISIP 4000psi, max press 6100psi, avg press 5780psi, 5min 3700psi, 10min 3600, 15min 3500, max rate 3.1 BPM, avg rate 2.8 BPM. RTTS @ 8350', RBP @ 8700'.

10-23-82 Move RTTS to ± 8550', perf 8608'-8612' w/4 shots/1, swab dry, prep to acidize.

10-24-82 Acidize w/1000 gal 7 1/2" Morrowflo Acid w/1000 SCF N<sub>2</sub>/BBL & ballsealers.

hereby certify that the foregoing is true and correct

SIGNED B. Stobbs TITLE Drilling & Production Manager DATE 10-25-82

(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY

OCT 26 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED

OCT 26 1982

MINERAL RESOURCES  
RECORDING SECTION