| Furm 3-330 | | oran e sa Cenval | Ū. S. | U. S. LAND OFFICE IRS JPUCES Serial Number UN8053 | | <u>Oruces</u> |
|--|---|---------------------------------------|---------------------------------------|--|------------------------------|----------------------------------|
| | traditional de la companya de la com La companya de la comp La companya de la comp | 14 <u>10</u> 00 | Seriai Lease | , NUMBER . or Permu | TO PROS | DD PECTUCESC |
| | Restricts | PARTI | T OF THE | INTER | IOR | |
| | | | CGICAL SURV | | | |
| | LCG | | L OR G | as v | VELI | _4 |
| LOCATE WELL CORRECTLY | | | | ~ ~ | | |
| Company ligner-Itz-Keye. | | | | | | |
| Lessor or Tract | | | | | | |
| Well No. <u>3-4</u> Sec. <u>20</u> T. 2 | | | | | | |
| Location .adOft. ${X \choose S}$ of Line a | ind 그요는 해. (분드 | of Line | e of | <u>LU</u> | Elevatic (Derrick floor 1 | n 2:00U elative to sea level) |
| The information given herewit so far as can be determined from al | h is a complete Lavailable reco | I | | | | |
| so far as can be determined from al | i avanabie recu | Signed. | | sit. | IT up | 121 |
| Date 120. 6 1986 | | | Titla Or | erato: | n â lin | <u>ncrer</u> |
| The summary on this page is fo | | | | | | |
| Commenced drillinge.g | <u>1935,</u> 19. | Finished | defiling <u>Jan</u> | <u>. 26 l</u> | 506 | , 19 |
| | OIL OR GAS | | ICHES | | | |
| No. 1, from | (<i>Je</i> 1400 G | note gas by G) No. 4, 1: | | t | 0 | |
| No. 2, from to | | | | | | |
| No. 3, from to . | | | | t | 0 | |
| | | | | | | |
| No. 1, from | 275 201 | II No. 3, ii | rom | t | 0 | <u> </u> |
| No. 2, from1185 to _ | <u>1200 </u> | No. 4, fi | | t | 0 | |
| · | | N a ne c ona | ; | | | |
| Size Weight Threads per Mak | | lind of slice - C | as and pulled from | Perfor From | To | Purpose |
| $\frac{1}{2} \frac{1}{2} \frac{1}{2} \frac{40}{3} \frac{3}{3}$ | | ····· | | | | |
| <u> </u> | <u>liest</u> | · · · · · · · · · · · · · · · · · · · | | | | |
| | | | | | | |
| | | | | | | |
| | UDDING AND | CEMENTIN | a record | | | |
| Size casing Where set Number sacks | of cement | Method used | Mud gravity | Amount of mud used | | ud used |
| 760 <u>1000</u> 10 | | | · · · · · · · · · · · · · · · · · · · | | | |
| / | · | | | - | | |
| | | | · | | | |
| | | | · · · · · · · · · · · · · · · · · · · | | | |
| | PLUGS. | and adapt | EZC | | | |

FOLD MARK

J