

MARBOB ENERGY CORPORATION
DELHI STATE 2
SEC 33 T17S R28E 990FWL 390FNL

=====

WELL HISTORY

=====

PBTD: 1966'

TD: 1970'

SP Csg: 8 5/8" 32# @ 500 C/w 35sx

LS Csg: 4 1/2" 9.5# @ 1968' C/w 75sx reg. Pozmix

T SALT: T YATES 430

T 7 RIVERS 708

B SALT: T QUEEN 1225

T GRAYBURG 1650

PERFS: 1922-34

T SAN ANDRES 1904

=====

COMPLETION REPORT

=====

10-22-61 Perfed csg at 1922-34 w/4 shot per foot. Frac w/21,000 gals and 350sx sand, and 100 gals acid.

10-23-61 Ran tbg to 1900. Circ sand. Swabbed hole. well kick off and flowed. Put on 3/8" choke. Well flowed 50 bbls and died.

10-24-61 Swabbed well off and flowing to tank battery. Potentialled at 39 bbls per day on 3/8" choke.

=====

WELL REPORT

=====

12-28-61 Re-fractured perfs 1922-34 w/32000 gals lease crude and 400sx

4-5-78 Clean out to 1957' with sand pump. Perforated csg at 695-715
Ran in hole with tbg.

4-6-78 Put back on pump

6-12-89 Rigged up pulled rods, Tried to pull tbg, pkr stuck, Parted
tbg, Pulled out hole with 46 jts tbg.

9-7-89 PROPOSE TO PLUG AND ABANDON AS FOLLOWS: Pkr stuck in hole,
at 950', Propose to set pkr as close to pkr as possible and
squeeze perfs 1922-34 with 100sx cmt, tag plug. Set 25sx plug