Form 9-381 a (March 1942)

23

Budget Bureau No. 42-R258.1. Approval expires 11-30-49.

Land Office Las Cruces 056302 B

Unit Johnson

to diana mudding inha a

## SUNDRY NOTICES AND REPORTS ON WELLS

SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	~~~~	SUPPLEMENTARY WELL HISTORY	
		1	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

		, 19	<u>49</u>		
Well No9_B is locat	<b>ted</b> <u>1980</u> ft. fro	om ${N \\ S \\ X}$ line a	nd <sup>1,980</sup> ft. from	$\left\{ \begin{matrix} \mathbf{E}^{\mathbf{X}} \\ \mathbf{W} \end{matrix} \right\}$ line of sec. $\mathbf{Z}$	34
SE-NW 34	16 S	<u>31 E</u>	NMPM (Meridian)		
(14 Sec. and Sec. No.)	(Twp.)	(Range)	•		
Square Lake (Field)	Eddy (County	or Subdivision)	NEW MEXICO (State or Territory)		

The elevation of the derrick floor above sea level is  $\frac{4024}{1000}$  ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths or proposed casings; indicate indicating jobs; construction of the sands; and all other important proposed work)
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed work) The $5\frac{1}{2}$ " oil string collapsed at 2020' against the tubing; every ossible effort has been made to pull this tubing, which is pulled nto at 2012'. Company tools have been on this job for 30 days, with cost exceeding \$3,000.00 for the job at present. Acid was used as final remedy, but with no results. We are asking permission to plug his well as follows: load hole to kill all gas, dump 20 sax of cement t $5\frac{1}{2}$ " pipe stub, fill hole with heavy mud to the base of 8 5/8" casing t 788', then set a 15 sax cement plug and fill with to the point at
hich the 8 5/8" casing will be knocked oil, the place a cement bridge lug and follow with beavy mud the the surface. Place a cement bridge nd regulation marker at the surface. This well has been on the pump for 3 years, and was producing
BOPD.
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.
Company G.B. Suppes
Address Box 151 Artesia, N.M. By 3E Kennedy
Artesia, N.M. By/32 /lenned/
Title Drilling Supt.

U. S. GOVERNMENT PRINTING OFFICE 10-8437-3