Form 9-331a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	Land Office	las.	Crue	96
	Lease No	<b>362</b> (	18-A	
4,5	Unit			
	30-01	5-	-06	168

NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<b>X</b>	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING.		SUPPLEMENTARY WELL HISTORY

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hitcheach	3		Novomber 23	19.56	
Well Nois located	1980 ft.	from $\begin{bmatrix} \mathbf{N} \\ \mathbf{X} \end{bmatrix}$ line	and 660 ft. from E line of sec.	23	
SB: NR: 23	16	<b>27</b>	N.M.P.W.		
SB: NR: 23  (4 Sec.and Sec. No.)  (LLLLLLL  (Field)	Ld	dy.	(Meridian)		
(Field)	(County or Subdivision) (State or Territory)				
The elevation of the derrick flo	oor above se	a level is	ft.		

## **DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and all other important proposed work)

As per our conservations of 11/21 and 11/23 1956 we purpose to test to the San Andres or not to exceed 2600'. We will set and mud 10° 00 casing at approximately 625' to shut off any surface water. If production is encountered we purpose to bridge hole, pull 10s OD casing and run 8 5/8" OD or 7" OD casing and cement same to surface, drill bridge and run 5 1/2" OD easing and cement with 100 sacks or back to 1500'. If we get good show of oil we purpose to sand frac and test.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.					
Company Tom Boyd					
Address102 South Second	- D.				
Artesia, New Mexico	By John S. Bamb				
	Title				