

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN PLICATE*
(Other instr. as on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-069465

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Stablein Federal

9. WELL NO.

10. FIRED AND POOL, OR WILDCAT

Henderson Area Wildcat

11. SEC. T., R., M., OR BLE. AND

SURVEY OR AREA
Sec. 10, T-16-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐ New Well

2. NAME OF OPERATOR

Shell Oil Company (Hastens Division) ✓

3. ADDRESS OF OPERATOR

P.O. Box 1509, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface1980' FNL & 660' FKL, Section 10, T-16-S, R-30-E, NMPM Survey
Eddy County, New Mexico

14. PERMIT NO.

-

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3865' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Ceg. Detail-Cement

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well
Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

July 7, 1967 thru July 9, 1967

Cemented 98 to (3087') 8 5/8", H-40, 32#, & J-55, 24#, 8rd thread, STAC, New, Lobster casing at 3100' w/400 sx Class "C". Cement circulated. Plug down at 8:45 AM (CDT) 7-9-67. After WOC 12 hrs tested casing to 2200 psi for 30 mins.

1. 472
2. Class "C" Cement
3. 600f
4. 910f
5. 500 Psi
6. 12 Hrs.

RECEIVED

AUG 7 1967

D. C. C.
ARTESIA, NEW MEXICORECEIVED
JUL 27 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *R. J. Doubek* R. J. DoubekTITLE Division Mechanical Engineer DATE July 24, 1967

(This space for Federal or State office use)

APPROVED BY
COMMISSIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
AUG - 4 1967
R. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations, when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.