

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>JATES PET. CO.</u>		Lease <u>JACKSON EST. B4</u>		Well # <u>#3</u>	
Location of Well <u>1650-S 990-W</u>	Unit <u>L</u>	Section <u>22</u>	Township <u>17</u>	Range <u>25</u>	County <u>EDDY</u>
Drilling Contractor <u>CACTUS DRILLING CO.</u>		Type of Equipment <u>ROTARY</u>			
APPROVED CASING PROGRAM <u>7-9-71</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>13 3/4"</u>	<u>10 3/4"</u>	<u>32#</u>	<u>USED</u>	<u>210'</u>	<u>CIR.</u>
<u>9 7/8"</u>	<u>7"</u>	<u>20#</u>	<u>USED</u>	<u>1150'</u>	<u>CIR.</u>
<u>6 7/8"</u>	<u>4 1/2" + 5 1/2" TAP.</u>	<u>9.5# 14#</u>		<u>450'- 1050'</u>	<u>CIR.</u>
Casing Data:					
Surface <u>37</u> joints of <u>7"</u> inch <u>20</u> # Grade <u>J-55 API US</u>					
Inspected by <u>APP</u> (Approved) (Rejected)					
Inspected by <u>O. K. Howe</u> date <u>7-12-71</u>					
Cementing Program					
Size of hole <u>9 7/8"</u> Size of Casing <u>7"</u> Sacks cement required					
Type of Shoe used <u>TEXAS</u> Float collar used Btm 3 jts welded <u>TAPE AND LOCK</u>					
TD of hole <u>1145</u> Set <u>1133</u> Feet of <u>7</u> Inch <u>20</u> # Grade <u>API J-55</u>					
Not used csg. @ <u>1145</u> with <u>325</u> sacks neat cement around shoe					
+ <u> </u> sax <u> </u> additives <u>2% Cal. Chloride</u>					
Plug down @ <u>1205</u> (AM) (PM) Date <u>7-13-71</u>					
Cement circulated <u>YES</u> No. of Sacks					
Cemented by <u>DEHON</u> Witnessed by <u>O. K. Howe</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date <u>7-14-71</u>					
Method used Witnessed by					
Remarks:					

CENT. 900'