

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
OCT 22 1971

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease:	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Morris Estate CC
3. Address of Operator 207 South 4th Street-Artesia, New Mexico 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>M</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3499' GL	12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER Perf. and Sand Frac ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1470' - Ran a tapered string of production casing as follows: Ran 444' of 5½" 9.5#, J-55 and 1009' of 5½" 14, J-55 casing (Total 1453') 1-swage and shoe set at 1470' with 135 sacks of Incor Neat 2% CaCl cement. Cement circulated. PD at 4:30 PM 10-11-71. Centralizers at 1430' 1310', 1190' and 1030'. WOC 24 hours and tested casing with 1000#. Tested OK.

Perforated as follows: 1413, 1409, 1393, 1385, 1374½, 1365, 1358, 1354, 1339, 1335, 1324, 1319, 1395½, 1391½, 1387, 1372, 1363, 1361, 1356, 1352, 1341½, 1337, 1326½, 1322.

Sand Frac'd using 4000 gallons of 15% regular acid for breakdown, 56000# 20-40 sand and 80000 gallons of treated water.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Gressett TITLE Engineer DATE 10-22-71

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE OCT 26 1971

CONDITIONS OF APPROVAL, IF ANY: