

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on re-  
verse side)Form approved  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

0236906

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mesa Federal

9. WELL NO.

No. 1

10. FIELD AND POOL, OR WILDCAT  
Wildcat11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

30-T17S-R24E

12. COUNTY OR PARISH

13. STATE

Eddy County

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☐ DRY HOLE

2. NAME OF OPERATOR

Estoril Producing Corporation

3. ADDRESS OF OPERATOR

1120 Vaughn Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface

1980' FSL &amp; 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3876' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The well was plugged and abandoned 10-08-74 with plugs set as follows:

7400' to 7300' with 40 sacks of Class H Cement, 6200' to 6100' with 40 sacks of Class H Cement, 4825' to 3725' with 40 sacks of Class H Cement, 3050' to 2950' with 40 sacks of Class H Cement, 1590' to 1490' with 40 sacks of Class H Cement, and 10 sacks of Class H Cement on surface. (Verbal approval received from USGS office Artesia on 10-08-74). Attached is cementing affidavit from B J, Inc. as well as Compensated Neutron-Formation Density and Dual Laterolog logs.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE Vice President

DATE 10-23-74

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

RECEIVED

OCT 24 1974

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICOAPPROVED BY  
MAY 8 1975  
J. L. BEEKMAN  
ARTESIA DISTRICT ENGINEERPOSTED  
ID-2  
2-7-75