

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND	FICE
OPER	OR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

AUG 22 1975

D. C. C.

ARTESIA, OFFICE

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

5a. Indicate Type of Well	State <input type="checkbox"/> Res <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Former Lease Name	Patterson "EL"
9. Well No.	1
10. Field, Road, or Wildcat	Und. Morrow
12. County	Eddy

1. Name of Operator	Yates Petroleum Corporation
3. Address of Operator	207 South 4th Street - Artesia, NM 88210
4. Location of Well	UNIT LETTER <u>M</u> , <u>880</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>31</u> TOWNSHIP <u>17S</u> RANGE <u>26E</u> NMPM.

15. Elevation (Show whether DF, RT, GP, etc.)
3442' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING Casing ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated dates of any proposed work) SEE RULE 1103.

Spudded 17½" hole at 10:30 AM 8-15-75.

TD 362' - Ran 8 joints of 13-3/8" 48# K-55 new casing (362') set at 360' KB. Cemented w/250 sacks Class C 4% CaCl. PD 5 PM 8-15-75. Cement circulated. WOC 12 hours, cut off landing joint and welded on nipple. NU and drilled cement, reduced hole to 12¼" and resumed drilling.

TD 1270' - Ran 31 joints of 8-5/8" 24# J-55 new casing (1271') set at 1269' KB. Cemented w/350 sacks Incor mix (6% Gilsonite, 0.6% flocele) 2% CaCl plus 250 sacks Class C 2% CaCl. PD 5:00 PM 8-17-75. Cement circulated. WOC 18 hours, cut off landing joint, nipples up, installed BOP's and tested to 1000#. OK. Drilled cement and tested shoe to 600#. OK. Reduced hole to 7-7/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

Engineer

8-22-75

APPROVED BY

TITLE

SUPERVISOR, DISTRICT II

DATE

AUG 22 1975

CONDITIONS OF APPROVAL, IF ANY: