

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND	FICE
OPER	OR

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 27 1976

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Well State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.		
7. Unit Agreement Name		
8. Farm or Lease Name Caffall "FD" Com		
9. Well No. 1		
10. Field, Pool, or Wildcat Und Kennedy Farms Morrow		
11. Elevation (Show whether DF, RT, GR, etc.) 3337' GR		
12. County Eddy		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	CASING TEST AND CEMENT LOG <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	OTHER Set Production csg & Perf. <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated completion date if proposed work) SEE RULE 1103.

TD 8670'; PBTD 8550'. Ran 47 joints of 5½" 17# K-L (1971'), 141 joints of 5½" 15.5# (5770'), 21 joints 17# 5½" K-L (882') (Total 8623') set at 8596' KB w/Guide Shoe, diff-fill float collar at 8550'. 6 centralizers and cemented w/500 gallons mud flush, 125 sacks Class H w/0.5% CFR-2 & 5# KCL, 210 sacks Hal-lite w/0.5% CFR-2 and 5# KCL and 90 sacks of Class H w/0.5% CFR-2 and 5# KCL, displaced w/40 bbls 2% KCL and 162 bbls fresh water. PD 3:45 PM 1-12-76. Set slips, backed off landing joint. Pressured up to 1700#. OK. Ran 2-3/8" tubing w/Tubing Conveyed Gun, perforating nipple 8352-54; Guiberson Uni-VI packer at 8346', On-off-tool w/Profile at 8345'. Perforated the Morrow 8402-06 & 8410-16 w/40 .34" holes (4JSPF). GTS in 2". Flowing 1360# on 1/2" choke.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 1-26-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JAN 28 1976

CONDITIONS OF APPROVAL, IF ANY: