

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Ltr Corp</i>		Lease <i>Hunter Ft. Conn.</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980 N 1940 W</i>	Section <i>15</i>	Township <i>17</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Red Oil Co.</i>			Type of Equipment <i>Rotary</i>		

* *Witness* APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>400</i>	<i>Cin.</i>
* <i>12 1/4"</i>	<i>8 5/8"</i>	<i>24</i>		<i>1400</i>	<i>"</i>
<i>7 7/8"</i>	<i>4 1/2" or 5 1/2"</i>			<i>8900</i>	<i>250</i>

Casing Data:
Surface 32 joints of 8 5/8 inch 24 # Grade API New K-55
(Approved) (Rejected)

Inspected by *Salma Medina* date *2-28-76*

Cementing Program
Size of hole *12 1/4"* Size of Casing *8 5/8"* Sacks cement required *500/sk*
Type of Shoe used *Tool Joint* Float collar used *2 ft. 1/2"* Btm *2* jts welded *Thread Lock*
TD of hole *1374' GL* Set *1360' GL* Feet of *8 5/8* inch *24* # Grade *K-55*
New-used csg. @ *1360' GL* with *150* sacks neat cement around shoe *Class C 2% cc*
+ *350* sack *Class C* additives *6% Alumina 6% Flocc 2% cc*
Plug down @ *8:15* (AM) (PM) Date *2-28-76*
Cement circulated *Yes* No. of Sacks *Contaminated Chit*
Cemented by *Denton* Witnessed by *Salma Medina*
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____
Casing test @ _____ (AM) (PM) Date _____
Method Used _____ Witnessed by _____
Checked for shut off @ _____ (AM) (PM) Date _____
Method used _____ Witnessed by _____
Remarks: *Surface 12 1/4" hole TD 405' KB at 391' GL Ran 10 jts*
13 3/8" 48# H-40 New Ant 250/sk Class C 4% cc
PD 10:00 PM 2-26-76 Cin 10/sk
Water 400-950, 1090-1284

Inte Port Fell back slowly. Note Fill to surface w/8 yds.
Ready Mix.

Centy. *584-1330* Basket *634-538*