

NO. OF COPIES RECEIVED		3
DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND	FILE	
OPER	OR	

NEW MEXICO OIL CONSERVATION COMMISSION

JUN 16 1976

Form O-100
Supersedes O-1
O-100 and O-101
Effective 1-1-66

O. C. C.

SUNDRY NOTICES AND REPORTS

ARTESIA OFFICE

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER A WELL OR TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL OR TO RE-ENTER A WELL" FOR SUCH PROPOSALS.

1. ☐ OIL ☐ GAS WELL ☐ OTHER	
2. Name of Operator Yates Petroleum Corporation	
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	
4. Location of Well UNIT LETTER <u>H</u> <u>660</u> FEET FROM THE <u>East</u> LINE AND <u>1980</u> FEET FROM THE <u>North</u> LINE, SECTION <u>29</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> MAP	

5. Indicate type of well Type ☐ Fee ☒
6. Well Name Gable "FV" Com
7. Unit Name 1
8. Designation Undesignated
9. County Eddy

10. Elevation (Show whether DF, RT, GP, etc.) 3588' GK

16. Check Appropriate Box To Indicate Nature of Notice Report or Other Operation	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT ON:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPER. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT ☐
OTHER ☐	OTHER ☒ Set Prod Csg & PB

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent data in feet and inches work) SEE RULE 1103.

TD 8190'; PBTD 6772'. - Verbal approval was given by Mr. Bill Gressett, Supervisor District #II, for the New Mexico Oil Conservation Commission to Plug Back as follows: 40 sacks of Class "C" cement 7800-7660'; 50 sacks of Class "C" cement 7100-6950'.

Ran 212 joints of 4½" OD 10.5# K-55 ST&C (6831') set at 6805' KB. Howco Guide shoe at 6805', Automatic fill float collar at 6772' and 3 centralizers at 6739, 6641, 6354, 5 Turbolizers at 6574, 6514', 6451, 5261, 5323'.

Preceded cement job w/500 gallons mud flush. Cemented by Halliburton w/265 sacks of Howco-lite w/5/10% CFR-2 + 5# KCL/sack followed w/200 sacks of Class "H" w/5/10% CFR-2 + 5#KCL/sack and displaced cement w/107.3 bbls fresh water. PD 6:00 PM 4-22-76. WOC and tested to 1500#. OK. Ran Temp. Survey and found top of cement at 4760'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNED <u>Christine Johnson</u>	TITLE <u>Geol. Secty</u>
DATE <u>6-15-76</u>	
APPROVED BY <u>W.A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>
DATE <u>JUN 16 1976</u>	
CONDITIONS OF APPROVAL, IF ANY:	