

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYN. M. C. A. W. S.
SUBMIT IN TRIP
(Other instruction
verse side)TIE
TOForm approved
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 054434

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "BQ"

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Bagle Creek (S.A.)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 27-17S-25E
Unit C

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

330' FNL & 1650' FWL of Sec. 27-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3537' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 1500'; PBTD 1483'. Ran 12 joints of 4½" 10.5# H-55 (496'), 24 joints of 5½" 15.5# J-55 (987') (Total 36 joints 1483') set at 1483'. 1-Guide shoe, centralizers at 1443, 1401, 1360, 1319 and 1278'. Cemented w/150 sacks of Class "C" cement. Cement circulated. PD 4:00 PM 3-30-76. WOC and tested to 1000#. CK.

Perforated 1303-1447' w/31 .45" holes as follows: 1st Stage: - 1306, 33½, 42, 47½, 57, 70, 75, 87, 99, 1405, 13, 20, 47 (13 holes). Acidized w/3000 gallons of 15% regular acid. 2nd Stage: - 1303, 15, 31, 39½, 45½, 54, 59, 68, 72½, 84½, 97, 1401, 03, 10, 16, 23, 25, 44' (18 holes). Treated all perforations w/60000 gallons of treated water and 100000# 20-40 sand.

RECEIVED
APR - 5 1976
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine J. Johnson

TITLE

Geol. Secty

DATE

4-5-76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
APR 6 - 1976
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side