

INSTRUCTIONS

This form is to be filled with the appropriate District Office of the Commission not later than 30 days after the completion of any newly drilled or reopened well. It shall be accompanied by one copy of all electrical and radioactivity logs run in the well and a summary of all special tests conducted, including stimulation tests. All log data reported shall be measured by the log in the case of conventionally drilled wells; true vertical depth shall be reported for multiple completion items, so that depth shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where only quadruplicate is required. See Rule 11.1.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 8125'	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka 8630'	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 454'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 975'	T. Simpson	T. Gallup	T. Ignacio Qtzite
T. Glorieta 2487'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb 3980'	T. Granite	T. Todillo	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo 4627'	T. Bone Springs	T. Wingate	T.
T. Wolfcamp 5900'	T. Morrow 8857'	T. Chinle	T.
T. Penn. 7695'	T. Chester 9134'	T. Permian	T.
T. Cisco (Bough C)	T. Yeso 2645'	T. Penn. "A"	T.
	Lower Morrow 8920'		
	Base Morrow 8986'		

SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.
No. 2, from.....to.....	feet.
No. 3, from.....to.....	feet.
No. 4, from.....to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
454'	975'	521'	Queen				
975'	2487'	1512'	San Andres				
2487'	2645'	158'	Glorieta				
2645'	3980'	1335'	Yeso				
3980'	4627'	647'	Tubb				
4627'	5900'	1273'	Abo				
5900'	7695'	1795'	Wolfcamp				
7695'	8125'	430'	Pennsylvanian				
8125'	8630'	505'	Strawn				
8630'	8857'	227'	Atoka				
8857'	8920'	63'	Morrow				
8920'	8986'	66'	Lower Morrow				
8986'	9134'	148'	Base Morrow				
9134'	TD	51'	Chester				