

RECEIVED

RECEIVED

CLSF

Form 3160-5 (June 1990)

MAY 11 10 55 AM '95

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

JUN 30 1995

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

OIL CON. DIV.

SUNDRY NOTICES AND REPORTS ON WELLS DIST. 2

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

United Meridian Corp. (Formerly General Atlantic Resources, Inc.)

3. Address and Telephone No.

410 17th Street, Suite 1400 Denver, CO 80202 (303) 573-5100

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FEL, Section 1-T16S-R27E

5. Lease Designation and Serial No.

NM-8436-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Diamond Mound Federal #2

9. API Well No.

30-015-22501

10. Field and Pool, or Exploratory Area

Atoka

11. County or Parish, State

Eddy NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent Subsequent Report Final Abandonment Notice

TYPE OF ACTION

Abandonment Reconpletion Plugging Back Casing Repair Altering Casing Other

Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water

(Note: Report results of multiple completions on Well Completions or Reconpletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

December 9 & 10, 1994. The well was plugged as follows:

- 1) Move in rig up wireline dump bailer, unflangewell head. 2) Pick up 50' of dump bailer and run in hole off mast trailer, mix and spot cement at the following depths and volumes approved by the BLM. 3) Set cement plugs with wireline dump bailer:

- 150' cement plug from 7085' to 7235' 150' cement plug from 4975' to 5125' 100' cement plug from 1418' to 1518' 100' cement plug from 298' to 398' 50' cement plug from surface to 50'

Part ID-2 7-21-95 P4A

- 4) Wellbore was plugged, BLM was notified (Joe Lara) but did not witness. 5) Well pad cleaned up.

Approved as to plugging of the well bore Liability under bond is retained until surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Regulatory Coordinator

Date 5/15/95

(This space for Federal or State office use)

Approved by (ORIG. SCD.) JOE G. LARA

Title PETROLEUM ENGINEER

Date 6/28/95

Conditions of approval, if any: