

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Collier + Collier</i>		Lease <i>Zait</i>			Well # <i>1</i>	
Location of Well	Unit <i>16505 330W</i>	Section <i>22</i>	Township <i>17</i>	Range <i>28</i>	County <i>Eddy</i>	
Drilling Contractor	<i>yucca Drilling Co.</i>		Type of Equipment <i>Rotary to start 8-9-78</i>			
<u>APPROVED CASING PROGRAM</u>						
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement	
<i>6 5/8"</i>	<i>4 1/2"</i>	<i>9.5</i>		<i>800</i>	<i>250</i>	
Casing Data:						
Surface <i>4 1/2</i> joints of <i>20</i> inch <i>9.5</i> # Grade <i>J-55</i>						
 <i>Yes</i> (Approved) (Rejected)						
Inspected by <i>B.W. Weaver</i> date <i>8-10-78</i>						
Cementing Program						
Size of hole <i>6 5/8</i> Size of Casing <i>4 1/2</i> Sacks cement required <i>250</i>						
Type of Shoe used <i>Guide</i> Float collar used <i>Insert</i> Btm 3 jts welded <i>Yes</i>						
TD of hole <i>800</i> Set <i>800</i> Feet of <i>4 1/2</i> Inch <i>9.5</i> # Grade <i>J-55</i>						
New used csg. @ <i>800</i> with <i>250</i> sacks neat cement around shoe						
+ <i>sax</i> <i>additives</i>						
Plug down @ <i>9:00</i> (AM) (PM) Date <i>8-10-78</i>						
Cement circulated <i>Yes</i> No. of Sacks <i>30 Sacks</i>						