

FILE	/	/
U.S.G.S.	/	/
LAND OFFICE		
OPERATOR	/	/

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

Supersedes Old
C-102 and C-103
Effective 1-1-65

FEB 14 1980

O. C. D.

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Goat Roper "LP" Com
9. Well No. 1 1
10. Field and Pool, or Wildcat Und.
12. County Eddy

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th Street - Artesia, NM. 88210

4. Location of Well
UNIT LETTER P 1130 FEET FROM THE South LINE AND 1300 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 17S RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3413'

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17½" hole at 9:30 AM 2-8-80.
Ran 9 joints of 13-3/8" 48# H-40 (368') of casing set at 365'. 1-Guide Shoe at 365'. Cemented w/360 sacks of Class C 4/10% CaCl. Slurry weight 14.8, 1.32 cu.ft/sack. Compressive strenght at 70 degrees 1023 psi in 12 hours. PD 9:00 PM 2-8-80. Circulated 25 sacks to surface. WOC 12 hours, backed off and reduced hole to 12¼", drilled plug and tested to 600#. OK and resumed drilling.
TD 1245' - Ran 31 joints of 8-5/8" 24# K-55 ST&C (1248') of casing set at 1245'. 1-guide shoe at 1245'. 1-insert float at 1205'. 1-centralizer at 1205'. Cemented w/430 sacks 65-35 Poz, 4% gel, 5# Kolite, 1/4#/sack celloflakes. Tailed in w/150 sacks Class C 2% CaCl. PD 3:30 PM 2-10-80. Cement did not circulate. WOC and ran Temperature Survey at 9:30 PM. Found top of cement at 520'. Ran 1" and tagged cement at 528'. Spotted 172 sacks of Class C 4% CaCl. Cement circulated 10 sacks to surface. PD 10:20 PM 2-10-80. WOC 18 hours, NU and tested to 1500#, OK. Reduced hole to 7-7/8", drilled plug and tested to 600#. OK and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. A. Gessert TITLE Geol. Secty. DATE 2-13-80

PROVED BY W. A. Gessert TITLE SUPERVISOR, DISTRICT 7 DATE FEB 15 1980

CONDITIONS OF APPROVAL, IF ANY: