

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Lykes Tech. Corp.</i>		Lease <i>Jackson Estate B4</i>		Well # <i>9</i>	
Location of Well	Unit <i>19803 990W</i>	Section <i>22</i>	Township <i>17</i>	Range <i>25</i>	County <i>Elddy</i>
Drilling Contractor <i>and Dril Co.</i>			Type of Equipment <i>Rotary & start approx. 2-5-80</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>320</i> <i>360</i>	<i>300 circ.</i>
<i>12 1/4"</i>	<i>8 5/8"</i>	<i>24</i>		<i>1160</i>	<i>550 "</i>
<i>7 7/8"</i>	<i>5 1/2" or 4 1/2"</i>	<i>10.5-11.6 15.5-17</i>		<i>8450</i>	<i>300</i>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required _____

Type of Shoe used *pattern* Float collar used *yes* Btm *3* jts welded *yes*

TD of hole *1168'* Set *1168'* Feet of *8 5/8* Inch *24* # Grade *K-55*

New-used csg. @ *1168'* with *20027cc* sacks neat cement around shoe

+ *460* sax *6 3/35* *por.* additives *6 # Kolite - 1/4 # cel. flakes - 4% gel - 3% cc*

Plug down @ *12830* (AM) (PM) Date *2/11/80*

Cement circulated *No* No. of Sacks *-0-*

Cemented by *Dowell* Witnessed by *Mike Stullfield*

Temp. Survey ran @ *8:30* (AM) (PM) Date *2/11/80* top cement @ *360'*

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

1. Ran 1168' Tagged Toc @ 371'

Pumped 220 sx class C

cement circulated

Full returns to 1168'

Last daily break @ 1040'