

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet. Corp.</u>		Lease <u>Gissler Av</u>		Well # <u>17</u>	
Location of Well	Unit <u>C</u>	Section <u>23</u>	Township <u>17</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>L & M Drilling Co.</u>		Type of Equipment <u>Rotary</u>		
* WITNESS					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 1/2"</u>	<u>10 3/4"</u>	<u>32 #</u>	<u>New</u>	<u>550</u>	<u>Circ</u>
* <u>9 1/2"</u>	<u>7"</u>	<u>23 #</u>	<u>"</u>	<u>1150</u>	<u>Circ.</u>
<u>6 1/4"</u>	<u>4 1/2"</u>	<u>9.5 #</u>	<u>"</u>	<u>TD</u>	<u>Circ.</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>9 1/2</u> Size of Casing <u>7</u> Sacks cement required _____					
Type of Shoe used <u>Tex-Pat</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1150</u> Set <u>1164</u> Feet of <u>7</u> Inch <u>23</u> # Grade <u>J-55</u>					
New- old csg. @ <u>1164</u> with <u>175</u> sacks neat cement around shoe					
+ <u>375</u> sax <u>Western life</u> additives _____					
Plug down @ <u>6:30</u> (AM) (PM) Date <u>3-17-83</u>					
Cement circulated <u>yes</u> No. of Sacks <u>40</u>					
Cemented by <u>Western</u> Witnessed by <u>B W Weaver</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Loss Zone @ 735</u> <u>Last Drilling Break 1048</u>					