

AC 505
623-6862

MARRS MUD

a division of
Corral, Inc.

1717 West Second St.
Roswell, New Mexico 88201

Sales Office
1118 West Aspen
Lovington, New Mexico 88260

AC 505
396-4876



COMPANY Depco, Inc.
WELL Coquina Fed. #1
FIELD _____
LOCATION Section 4, T-16-S, R-28-E
COUNTY Eddy STATE New Mexico
PROPOSED DEPTH 9,400'

PROPOSED MUD PROGRAM

CASING PROGRAM:

13 3/8"	Surface	@	575'
8 5/8"	Intermediate	@	1,950'
4 1/2"	Production	@	9,400'

SUGGESTED MUD PROPERTIES

DEPTH (FEET)	MUD WEIGHT (PPG)	VISCOSITY (SEC)	FLUID LOSS (ML)
100	8.8 - 9.0	32 - 34	No Control
300	9.2 - 9.4	32 - 34	No Control
575	9.2 - 9.4	32 - 34	No Control

Set 13 3/8" Surface Casing @ 575'. Drill out with brine water.

600	10.0	28	No Control
800	10.0	28	No Control
1,000	10.0	28	No Control
1,200	10.0	28	No Control
1,400	10.0	28	No Control
1,600	10.0	28	No Control
1,950	10.0	28	No Control

Set 8 5/8" Intermediate Casing @ 1,950'. Drill out with fresh water.

2,000	8.4	28	No Control
3,000	8.4	28	No Control
4,000	8.4	28	No Control
5,000	8.4	28	No Control
5,400	8.8 - 9.0	38 - 40	No Control
6,000	8.8 - 9.0	38 - 40	No Control
7,000	8.8 - 9.0	38 - 40	No Control
7,500	9.1 - 9.3	43 - 45	15 - 20
8,000	9.1 - 9.3	43 - 45	15 - 20
8,500	9.1 - 9.3	43 - 45	15 - 20
9,000	9.3 - 9.5	43 - 45	10
9,400	9.3 - 9.5	48 - 50	10

Set 4 1/2" Production @ 9,400'.