		~	UST
	NM OI	L CONS. COMM1 ION	
Form 9-331 (May 1963)	UNITED STATES Drawe DEPARTMENT OF THE INTER	T DDSUBMIT IN TRIPLICATE.	Form approved. Budget Bureau No. 42-R1424.
		OR White and SIL	5. LEASE DESIGNATION AND SERIAL NO. NM-036191
	GEOLOGICAL SURVEY		IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this	IDRY NOTICES AND REPORTS C s form for proposals to drill or to deepen or plug b Use "APPLICATION FOR PERMIT" for such pr		. IF INDIAN, ADDOTTED OR TRIDE NAME
1.			7. UNIT AGREEMENT NAME
WELL X WELL	OTHER	0CT 2 7 1982	· · · ·
2. NAME OF OPERATOR			8. FARM OR LEASE NAME Federales BO
Yates Petroleum Corporation		OIL & GAS	9. WILL NO.
		MINERALS MGMT. SERVICE	12
207 South 4th St., Artesia, NM 88210 4. LOCATION OF WELL (Report location clearly and in accordance with any S		State regeleration MEXICO	10. FIELD AND POOL, OR WILDCAT
See also space 17 be At surface			Eagle Creek SA
330 F	NL & 990 FEL, Sec. 22-T17S-R25	^E NOV 2 1982	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
		NUA 2 120E	SURVEY OR AREA
		O. C. D.	Unit A, Sec. 22-17S-25E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF	, RT, GR, etc.) ARTESIA, OFFICE	12. COUNTY OR PARISH 13. STATE
	3516' GR		Eddy NM
16.	Check Appropriate Box To Indicate N	lature of Notice, Report, or O)ther Data
	NOTICE OF INTENTION TO :		ENT REPORT OF:
TEST WATER SHUT-	OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other)	
(Other)		(NOTE: Report results Completion or Recomple	of multiple completion on Well etion Report and Log form.)
nent to this work.)		t details, and give pertinent dates, tions and measured and true vertica	including estimated date of starting any 1 depths for all markers and zones perti-
oudded a 14-3/4"	hole at 3:15 PM 10-17-82. Ra	n 9 jts of 10-3/4" 40	.5# J-55 ST&C casing set
	Pattern guide shoe set at 342		
/225 sacks Class	C with 3% CaCl ₂ . Compressive	strength of cement -	1275 psi in 12 hrs. PD
	Bumped plug to 1000 psi, rel		
	ks. WOC. Drilled out 10:30 PM		
n flow nipple.	Reduced hole to 9-7/8". Dill1	ed plug and resumed d	rilling. Ran 9 jts of
	casing set at 1157'. 1-Texas		
	13'. Cemented w/300 sacks Pac		
	aCl2. Tailed in w/150 sacks C released pressure and float h		
	ture Survey and found top of c		
	lass C 3% CaCl ₂ . PD 11:00 PM		
	25 sacks Class C 3% CaCl ₂ . PD		
	Spot'd 25 sacks Class C 3% CaC		
agged cement at	350'. Spot'd 25 sacks Class C	3% CaCl2. PD 6:30 A	M 10-20-82. WOC 2 hrs.
an l". Tagged c	ement at 300'. Spot'd 125 sac	ks Class C 3% CaCl ₂ .	PD 9:15 AM 10-20-82.
ement circulated	25 sacks to pit. WOC. Drill	ed out 11:15 AM 10-20	-82. WOC 19 hrs & 15 min.
ippled up and te	sted to 1500 psi, okay. Reduc	ed hole to 6-1/4". D	rilled plug and resumed
rilling.			

18. I hereby ceptify that the foregoing is true and correct	E	
signer ant a ditt	TITLE Engineering Secretary	DATE 10-26-82
(This space for Federal of State office use) (This space for Federal of State office use) (ORIG. SGD.) DAVID R. C (ORIG. SGD.) DAVID R. C (ORIG. SGD.) DAVID R. C	LASS TITLE	DATE
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO *S	See Instructions on Reverse Side	