

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate*
(Other instructions on reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug well to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | | |
|--|--|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | | 5. LEASE DESIGNATION AND SERIAL NO. NM-54425 | |
| 2. NAME OF OPERATOR Fred F. Pool, III ✓ | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | |
| 3. ADDRESS OF OPERATOR 5 Summer Wind Place, Roswell, NM 88201 | | 7. UNIT AGREEMENT NAME | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1880' FSL & 1830' FWL | | 8. FARM OR LEASE NAME Ronadero 9 USA | |
| 14. PERMIT NO. | | 9. WELL NO. #1 | |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4,085 GR | | 10. FIELD AND POOL, OR WILDCAT Square Lake N-Grbg/S.A. | |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 9, T16S, R31E | |
| | | 12. COUNTY OR PARISH Eddy | |
| | | 18. STATE NM | |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Commence Drilg & 8 5/8" casing X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-27-84 Spudded well at 5:00 p.m.

7-28-84 T.D. 380'. Ran 380' of 8 5/8", 24# casing, with insert float valve and regular guide shoe. Cemented with 200 sx class "c", 2% CaCL. Circulated 25 sx to surface. Plug down @ 4:00 a.m. WOC 18 hrs. Pressure tested to 1000 psi for 30 minutes, held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

Fred F. Pool, III

TITLE

Operator

DATE

8-3-84

(This space for Federal or State office use)

APPROVED BY

LWC

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

Paul

NEW MEXICO

*See Instructions on Reverse Side