

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

FORM APPROVED

(See other instructions on reverse side)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐

2. NAME OF OPERATOR

DEVON ENERGY CORPORATION (NEVADA)
20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611

3. ADDRESS AND TELEPHONE NO.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface 1090' FNL & 330' FWL; Unit "M"

At top prod. interval reported below (SAME)

At total depth (SAME)

5. LEASE DESIGNATION AND SERIAL NO.

LC-067849

N.M. Oil Cons. Division
811 S. 1st Street
Alamogordo, NM 88210-2834

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NA

7. UNIT AGREEMENT NAME

NA

8. FARM OR LEASE NAME, WELL NO.

Eagle "34M" Federal #25

9. API WELL NO.

30-015-29114

10. FIELD AND POOL, OR WILDCAT

Red Lake (Q-GB-SA)

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

"M" Section 34-17S-27E

14. PERMIT NO.

DATE ISSUED

8/19/96

12. COUNTY OR PARISH

Eddy County

13. STATE

NM

15. DATE SPUDDED

12/14/96

16. DATE T.D. REACHED

12/18/96

17. DATE COMPL. (Ready to prod.)

1/12/97

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

KB 3549'; GL 3544'; DF 3548'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

2599'

21. PLUG, BACK T.D., MD & TVD

2555'

22. IF MULTIPLE COMPL., HOW MANY*

NA

23. INTERVALS

DRILLED BY

ROTARY TOOLS

X

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

San Andres - 1790-2251'

25. WAS DIRECTIONAL SURVEY

MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

LDT/CNL/DLL/MSFL/GR; CBL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8-5/8" J-55	24#	1088'	12-1/4"	surf; 300 sxs lite & 200 sxs "C"	NA
5-1/2" J-55	15.5#	2599'	7-7/8"	surf; 150 sxs lite C & 375 sxs "C"	NA

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-7/8"	2164'	(OET)

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

1790-1897' ALPHA (7 - .40" EHD holes)

1979-2044' "A" (7 - .40" EHD holes)

2062-2134' "B" (8 - .40" EHD holes)

2158-2194' "C" (5 - .40" EHD holes)

2214-2251' "D" (4 - .40" EHD holes)

32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1790-2251'	2500 gals of 15% NeFe acid,
1790-2251'	1,000 gals PrePad + 2 drum Pro-Kem scale inhibitor
	180,000 gals gel water + 6000# 100 mesh sand +
	100,000# 20/40 Brady sd and 143,000# 16/30 Sand

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTIONS METHOD (Flowing, gas lift, pumping—size and type of pump)	WELL STATUS (Producing or shut-in)
1/20/97	Pumping (2-1/2" x 2" x 12' RWTC Pump)	Producing

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL.	GAS-MCF.	WATER-BBL.	GAS-OIL RATIO
2/4/97	24			84	42	342	500/1
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL.	GAS-MCF.	WATER-BBL.	OIL GRAVITY-API (CORR.)	
			84	42	342	38	

34. DISPOSITION OF GAS (Solid, used for fuel, vented, etc.)

Vented (To be connected)

35. LIST OF ATTACHMENTS

Logs, Deviation Surveys

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED *[Signature]*DIANA KEYS
TITLE ENGINEERING TECHNICIAN

DATE February 14, 1997

* (See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Premier Sand San Andres	1451'	1499'	sandstone dolomite	Bowers	608'	+2941
	1499'	2599'		Queen	798'	+2751
				Grayburg	1216'	+2333
				Premier	1451'	+2098
				San Andres	1499'	+2050