

30-015-29133

H-35-1728

Arco Permian / ALTOIA.

Evelyn 35 57 Com. #1

Recommended PLH Procedure, 2-4-99 / M.S.

FAX 915-523-6230.

TOPS

B. Salt 590'

T. Yates 715'

T. N. R's - 988'

T. Pucan - 1605'

T. S.A. - 2410'

T. B.S. - 4640' *

T. W.C. - 6840' *

T. Cisco 8992'

T. Canyon 9250'

T. Strawn - 9455'

T. Atoka - 10090'

T. Miss 10725'

* 10580 surface.

* 100' cmt Plug 522' TAG. 592'

* 100' cmt Plug 2870' TAG

* 100' cmt Plug 50' + 50' out csg 570h TAG TOC-3490' CBL.

* Free point + cut 5 1/2" csg.

* 255x - 4690' B.S.

* 255x 6890' W.C.

* Ex. CIBPO 9600' w/35 cmt 6-30-97.

13 3/8" - 522'
circ.

9 5/8" - 2820'
circ.

Window - 9677-90'

CIBPO 9600' w/35 cmt

9565'

Well PSI-Test TA 90 - 200'

CIBP - 10520' w/35 cmt. 12-17-96

T. Perf. 10,520'

5 1/2" - 10805' TOC-3490' CBL

TD 10667

cm plug 9772'-9548'
cm plug 9804'-9690'