

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Artesia, NM 88210

Expires August 31, 1985

LEASE DESIGNATION AND SERIAL NO.

LC-029426-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H. E. West "B"

9. WELL NO.

19

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec.10-T17S-R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

AUG 28 '89

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER ☒ WIW

2. NAME OF OPERATOR  
Hondo Oil & Gas Company

3. ADDRESS OF OPERATOR  
P. O. Box 2208, Roswell, NM 88202  
ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface  
660' FNL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3934' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) ran tbgs. & pkr.

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/07/89 Perforated 3821-3941' with 22 holes. Acidized 3821-3941' with 3000 gal. 15% NEFE acid. Flowed well back.

8/08/89 Reacidized 3821-3941' with 6000 gal. 20% CRA acid. Swabbed well back.

8/09/89 Perforated 3610-3792' with 28 holes. Acidized 3610-3792' with 4000 gal. 15% NEFE acid. Swabbed well back.

8/10/89 Frac'd 3610-3792' with 25,000 gal. cross-linked gelled water + 9200# 20-40 sand. Swabbed and flowed well back.

8/13/89 Perforated 3373-3569' with 39 holes. Acidized 3373-3569' with 6000 gal. 15% NEFE acid. Swabbed well back.

8/16/89 Ran 110 jts. 2 3/8" fiberglass tubing and a Guiberson ER-6 packer. Set both @ 3279'. Ready for injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineering Technician

DATE 8/16/89

(This space for Federal or State office use)

APPROVED BY (ORIG. SCD) DAVID R. GLASS

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

See Instructions on Reverse Side