

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Operations Division

311 S. 1st Street

Albuquerque, NM 87102-2894

FORM APPROVED

Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1880'FSL & 660'FEL of Section 18-T17S-R31E

5. Lease Designation and Serial No.

LC-029395A

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or CA, Agreement Designation

NA

8. Well Name and No.

Turner "A" #30

9. API Well No.

30-015-05228

10. Field and Pool, or Exploratory Area

Grayburg-Jackson Field

11. County or Parish, State

Eddy County, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged and abandoned as follows:

11/19/97 to 11/20/97 - Cut off stuck tubing @ 1891'. Pulled out of hole with free tubing.

11/21/97 to 11/22/97 - Set CIBP @ 1840'. Ran CBL and found TOC behind 7" csg @ 1240'. Shot 4 squeeze perfs @ 1180'. Spotted 10 sx cement. Set cement retainer @ 1130' & pumped 200 sxs "C". Shot 4 squeeze holes @ 580' and squeezed with 200 sx "C".

11/24/97 to 11/25/97 - Cemented to surface on 8 5/8" & 7" casing. Cut off 8 5/8" well head. Installed dry hole marker. Cleaned location.

Post ID-2
2-20-98
P & H

14. I hereby certify that the foregoing is true and correct

Signed Karen Byers
(This space for Federal or State office use)

Karen Byers

Title Engineering Technician

Date December 2, 1997

Approved by (MARK SGA) DAVID R. GLASS

Title _____

Date DEC 11 1997

Conditions of approval, if any:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

100 DEC -5 A 9 54

100 DEC -5 A 9 54

100 DEC -5 A 9 54