clsf

FORM APPROVED UNITED STATES Form 3160-5 DEPARTMENT OF THE INTERIOR NM OIL CONS COMMISSION Budget Bureau No. 1004-0135 (June 1990) Expires: March 31, 1993 BUREAU OF LAND MANAGEMENTDrawer DD 5. Lease Designation and Serial No. Artesia, NM 88210 LC-029395-A SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. N/A Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE N/A 1. Type of Well V Oil Well Gas Well 8. Well Name and No. 2. Name of Operato Turner "A" #25 Socorro Petroleum Company 9. API Well No. RECEIVED 3. Address and Telephone No. 30-015-05276 20 N. Broadway, Suite 1500, Oklahoma City, OK 73102 (405)552-4560 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Fren Seven Rivers JUL 15.'94 11. County or Parish, State 990' FNL & 2310' FEL, Section 19-T17S-R31E Eddy County, New Mexico O. C. D. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Non-Routine Fracturing Temporarily Abandon 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pert eed date of starting any proposed work. If well is directionally drilled. asured and true vertical depths for all markers and zo Plans are to temporarily abandon this wellbore by testing the 7" production casing and repairing any leaks. The production casing will then be tested to 500 psig. This test will be witnessed by a BLM representative. In lieu of plugging this well, it is requested that it be granted a temporarily abandon status following the above described work including the passing of a 500 PSIG Mechanical Integrity Test. This wellbore is located within an active Grayburg-Jackson waterflood project and is a deepening candidate during the infill development program now being evaluated and implemented. The well's current completion interval, the Seven Rivers, also appears to have secondary recovery potential. Plugging this well would necessitate it being redrilled at a future date. 711 14. I hereby certify that the foregoing is true and correct Randy Jackson, District Engineer PETROLEUM ENGINEER Test to be performed with

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

BUREAU OF LAND MANAGEMENT CARLSBAD RESOURCE AREA

Temporary Abandonment of Wells on Federal Lands

Conditions of Approval

According to 43 CFR 3162.3-4-c, " No well may be temporarily abandoned for more than 30 days without the prior approval of the authorized officer".

Temporary Abandonment (TA) status approval requires a successful casing integrity test as follows:

- 1. Contact the appropriate BLM office at least 24 hours prior to the scheduled Casing Integrity Test. For wells in Eddy County call (505) 887-6544; for wells in Lea County call (505) 393-3612.
- A bridge plug or packer shall be set at a maximum of 50 feet above any open perforations or open hole.
- 3. All downhole production/injection equipment (tubing, rods, etc.) shall be removed from the casing if they are not isolated by a packer.
- 4. The production casing shall be filled with corrosion inhibited fluid and pressure tested to 500 psi. The casing shall be capable of holding this pressure for at least 30 minutes with a 10% allowable leak-off.

Wells that successfully pass the casing integrity test will be approved for Temporary Abandonment (TA) status for 12 months provided that the operator:

- 1. Submits a subsequent Sundry Notice requesting TA approval,
- 2. Attaches a clear copy or the original of the pressure test chart,
- 3. And attaches a detailed justification why the well should not be plugged and abandoned.

The TA status could be extended without another casing integrity test provided there was no leak-off during the test.

If the well does not pass the casing integrity test, then the operator shall within 30 days submit to BLM for approval one of the following:

- 1. A procedure to repair the casing so that a TA approval can be granted.
- 2. A procedure to plug and abandon the well.