

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC-029418 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

RECEIVED

2. NAME OF OPERATOR

AUG 30 1972

3. ADDRESS OF OPERATOR

P. O. Box 1351, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

ARTESIA, OFFICE

14. PERMIT NO. **660' FSL and 660' FEL Sec. 11-17S-31E**

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3952' DF

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lea "C"

9. WELL NO.

13

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11-17S-31E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & set 8-5/8" casing
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Spudded 11" hole at 2:15 p.m. 8-21-72.
- 2) Drilled to 635' at 7:45 p.m. 8-21-72.
- 3) Ran 15 jts. (624') of 8-5/8" OD 24# J-55 condition "A" casing and set from 11' to 635'; guide shoe at 635' float collar at 593'; centralizers at 550' and 593'.
- 4) Cemented with 250 sacks Class "C" with 4% gel and 1/4# Celloflakes per sack and 125 sacks Class "C" cement with 2% calcium chloride. Pumped plug to 593'. Cement circulated.
- 5) After WOC 18 hours, tested 8-5/8" casing to 1000# for 30 minutes; held OK.
- 6) Drilled out cement. Resumed drilling 7-7/8" hole.

18. I hereby certify that the foregoing is true and correct

SIGNED

(Signed) **J. R. Avent**

J. R. Avent

TITLE **District Admin. Coordinator**

DATE **August 23, 1972**

(This space for Federal or State office use)

TITLE

DATE

*See Instructions on Reverse Side

