DEC. 1973  UNITED STATES  DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, use form 9-331-C for such proposals.)  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, use form 9-331-C for such proposals.)  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, use form 9-331-C for such proposals.)  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, use form 9-331-C for such proposals.)  To UNIT AGREEMENT NAME  8. FARM OR LEASE NAME E-prire South Deep Unit  9. WELL NO.  5. IEASE  N.M.—0555569  6. IF INDIAN, ALLOTTEE ON THE E-prire South Deep Unit  9. WELL NO.  5. IEASE  N.M.—OF LEASE NAME E-prire South Deep Unit  9. WELL NO.  10. FIELD OR WILLDCAT NAME SOUTH Empire — Morrow  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  AREA  12. II. API NO.  13. 1-17-20  14. API NO.  14. API NO.  15. ELEVATIONS (SHOW DF, KDB, AND WD) 3640' ICL  15. ELEVATIONS (SHOW DF, KDB, AND WD) 3640' ICL  16. COUNTY OR PARISH 13. STATE Eddy  NM  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details, and 6470'. Found hole at approximately 6470'. Ran cement retailer and tubing to 6430'. Sulvery	- N.M.O.C.D. COP	Y cist
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY  SUNDRY NOTICES AND REPORTS ON WELLS  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form to proposals to define or deepen or plug back to a different service, the Front soll proposals of the deepen or plug back to a different service, the Front soll proposals of the deepen or plug back to a different service, the Front soll proposals of the deepen or plug back to a different service, the Front soll proposals of the deepen or plug back to a different service, the Front Soll proposals of the service, the Front Soll proposals of the service service, the service service service service service, the service servi		Form Approved.
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals) to drill or to deepen or plug back to a different reservoir. Use from 3-311-Cfor uproposals.)  1. oil gas word of operator Amoco Production Company  3. ADDRESS of OPERATOR ADDRESS of OPERATOR A LOCATION OF WELL (REPORT LOCATION CLEARLY, see space 17 below). AT TOP PROD. INTERVAL: (Unit 6, SM/4, NE/4) AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SHAPEN WELL USA ALDRESS OF OPERATOR SUBSEQUENT REPORT OF: LEST WATER SHUT-OFF CHANGE SHAPE SH	UNITED STATES	5. LEASE
SUNDRY NOTICES AND REPORTS ON WELLS  (00 not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use form 3-31-C for such proposals.)  1. cil	DEPARTMENT OF THE INTERIOR	NM-0555569
## SUBURT NUILES AND REPORTS ON WELLS  ### SUBURT NUILES AND REPORTS ON WELLS  ### DATE OF THE PROPOSED OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertigopt of the depths for all markers and zones pertinent to this work.)*  ### SUBCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertigopt dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface including setting and true vertical depths for all markers and zones pertinent to this work.)*  ###################################	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1. oil well	(Do not use this form for proposals to drill or to deepen or plug back to a different	
2. NAME OF OPERATOR  AMOCO Production Company  3. ADDRESS OF OPERATOR  4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below)  AT TOTAL DETTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF:  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertugget dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface IOCATION and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Pan cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Nashed sand off bridge plug plug Plue plue plue plue plue plue plue plue p	reservoir. Use Form 9–331–C for such proposals.)	
2. NAME OF OPERATOR AMOCO Production Company 3. ADDRESS OF OPERATOR P. O. Box 68 Hobbs, NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 1980' FNL X 2180' FEL, Sec. 31 AT TOP PROD. INTERVAL: (Unit 6, SW/4, NE/4) AT TOTAL OEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3640' GL  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertingent dates.  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by settling packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pull. Pull		
Amorco Production Company  3. Address of operator  P. O. Box 68 Hobbs, NM 88240  4. Location of Well (Report Location Clearly, See space 17 below)  AT SUBFACE: 1980' FNL X 2180' FEL, Sec. 31 AT TOP PROD. INTERVAL: (Unit 6, SW/4, NE/4)  AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF FRACTURE TREAT  SHOOT OR ACIDIZE  PULL OR ALTER CASING  MULTIPLE COMPLETE  OLIVIE OR SUBSEQUENT REPORT OF:  ARTESIA, REW MELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  ARTESIA, REW MELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  ARTESIA, REW MELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  ARTESIA, REW MELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  ARTESIA, REW MELL  MOVED in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by settinn packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate hole by settinn packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	well well AA other	·1
3. ADDRESS OF OPERATOR P. O. BOX 68 Hobbs, NM 88240 1. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 1980' FML X 2180' FEL, Sec. 31 AT TOP PROD. INTERVAL: (Unit 6, SW/4, NE/4) AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND WD) 3640' GL  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertigent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and five pertigent dates measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by settinn packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 1980' FNL X 2180' FEL, Sec. 31 at 172-20 AT SURFACE: 1980' FNL X 2180' FEL, Sec. 31 at 170-PROD. INTERVAL: (Unit 6, SW/4, NE/4) AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15ST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE FRACTURE TREAT SHOOT OR ACIDIZE WILL DOR ALTER CASING WILL PULL OR ALTER CASING WILL PULL OR ALTER CASING WILL PULL OR ALTER CASING O(other)  ARTESIA, NEW MEXICO  ARTESIA, New Mitchiol  ARTESIA, N	Amoco Production Company 🗸	-[
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  AT SURFACE: 1980' FNL X 2180' FEL, Sec. 31  AT TOP PROD. INTERVAL: (Unit 6, SW/4, NE/4)  AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND WD)  3640' GL  15. ELEVATIONS (SHOW DF, KDB, AND WD)  3640' GL  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OR:  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pently diffled, give subsurface locations and FICE measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge pluq, packer, and tubing. Set bridge pluq at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge pluq. Pulled bridge pluq and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	3. ADDRESS OF OPERATOR	
AREA  AREA  AREA  Below.)  AT SURFACE: 1980' FML X 2180' FEL, Sec. 31  AT TOP PROD. INTERVAL: (Unit 6, SW/4, NE/4)  AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  DULL OR ALTER CASING  MULTIPLE COMPLETE  DULL OR ALTER CASING  MULTIPLE COMPLETE  AREA  AREA  31-17-29  12. COUNTY OR PARISH  13. STATE  Eddy  NM  14. API NO.  15. ELEVATIONS (SHOW DF, KDB, AND WD)  3640' GL  15. ELEVATIONS (SHOW DF, KDB, AND WD)  3640' GL  TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  DULL OR ALTER CASING  MULTIPLE COMPLETE  DULL OR ALTER CASING  MULTIPLE COMPLET		
AT SURFACE: 1980' FNL X 2180' FEL, Sec. 31 AT TOP PROD. INTERVAL: (Unit 6, SW/4, NE/4) AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND WD)  3640' GL  16. CHECK APPROPAL TO: SUBSEQUENT REPORT OF:  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertigent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Est
AT TOP PROD. INTERVAL: (Unit 6, SW/4, NE/4) AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND WD) 3640' GL  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  17. DESCRIBE TREAT  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF:  18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT OF NOTHER PARK OF NOTICE. REPORT OF NOTICE. REPORT OF NOTICE. REPORT O	below.)	31-17-29
AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND WD)  3640' GL  15. ELEVATIONS (SHOW DF, KDB, AND WD)  3640' GL  16. CHANGE SHUT-OFF  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent datails, and give pertinent datails, and give pertinent datails, and give pertinent to this work.)*  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent datails, and give p		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF		Eddy Nr
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF		14. API NO.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:    3640' GL     3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   3640' GL   364		
TEST WATER SHUT-OFF SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF SHOUL OR ACIDIZE  SHOOT OR ACIDIZE  SHOOT OR ACIDIZE  SHOOT OR ACIDIZE  SHOUL OR ACIDIZE  MULTIPLE COMPLETE  CHANGE ZONES  OR ARTESIA, NEW SEASON  (other)  TO DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertingent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and fice measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	REPORT, OR OTHER DATA	1
TEST WATER SHUT-OFF FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  PULL OR ALTER CASING	PROJECT FOR APPROVAL TO: CHECCOLINE REPORT OF	3640' GL
FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)  MOVED IN SECURISE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates and frue vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	TEST WATER SHATOSE	*·
REPAIR WELL PULL OR ALTER CASING WILLIPLE COMPLETE CHANGE ZONES ABANDON* (other)  ARTESIA, NEW MEXICO ARTESIA, NEW MEXICO ARTESIA, New Mexico including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and fice measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	TEST WATER SHUT-OFF	7 / Lat 1
REPAIR WELL PULL OR ALTER CASING WILLIPLE COMPLETE CHANGE ZONES ABANDON* (other)  ARTESIA, NEW MEXICO ARTESIA, NEW MEXICO ARTESIA, New Mexico including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and fice measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	SHOOT OR ACIDIZE	A second states
MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)  ARTESIA, NEW MEXICO ARTESIA, NEW MEXI		
CHANGE ZONES  ABANDON* (other)  ARTESIA, NEW MEXICO  ARTESIA, NEW MEXICO	PULL OR ALTER CASING	1000 change on Form 9-330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and FICE measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge pluq, packer, and tubing. Set bridge pluq at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge pluq. Pulled bridge pluq and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.  Subsurface Safety Valve: Manu. and Type	MULTIPLE COMPLETE	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and FICE measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge pluq, packer, and tubing. Set bridge pluq at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge pluq. Pulled bridge pluq and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.  Subsurface Safety Valve: Manu. and Type	CHANGE ZONES	JUI 3 1000 =
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and FICE measured and true vertical depths for all markers and zones pertinent to this work.)*  Moved in service unit 5-30-80. Ran retrievable bridge pluq, packer, and tubing. Set bridge pluq at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge pluq. Pulled bridge pluq and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.  Subsurface Safety Valve: Manu. and Type	(ether)	EM MEXICO
Moved in service unit 5-30-80. Ran retrievable bridge plug, packer, and tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.	AKILOM	0.00
tubing. Set bridge plug at 10,702' and test casing up the hole by setting packer at intervals 8110', 8016', 7263', 7138', and 6470'. Found hole at approximately 6470'. Ran cement retainer and tubing to 6430'. Squeeze cement down tubing with 700 sacks Class C cement. Circulate 100 sacks. Drill out cement retainer and cement. Washed sand off bridge plug. Pulled bridge plug and ran on/off tool and tubing. Set on/off tool at10,739'. Swab well and returned well to production. Production after workover in 24 hrs. was 45 bbls. condensate, 5 BW, and 1426 MCF.  Subsurface Safety Valve: Manu. and Type	including estimated date of starting any proposed work. If well is o	firectionally drilled, give subsurface locations and tile
	tubing. Set bridge plug at 10,702' and tessetting packer at intervals 8110', 8016', hole at approximately 6470'. Ran cement resqueeze cement down tubing with 700 sacks Drill out cement retainer and cement. Was bridge plug and ran on/off tool and tubing Swab well and returned well to production.	st casing up the hole by 7263', 7138', and 6470'. Found etainer and tubing to 6430'. Class C cement. Circulate 100 sacks. hed sand off bridge plug. Pulled . Set on/off tool at10,739'. Production after workover in
	Subsurface Safety Valve: Manu. and Type	Set @ Ft.

TITLE Ast. Ad. Analyst DATE 6-27-80

014 USGS-A