

RECEIVED

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

NOV 3 1982

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

O. C. D.
ARTESIA OFFICE
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ PxA

2. NAME OF OPERATOR
Amoco Production Company ✓

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 760' FSL X 2310' FEL, Sec. 30
AT TOP PROD. INTERVAL (Unit 0, SW/4, SE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE LC-062407	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Empire South Deep Unit	
9. WELL NO. 7	
10. FIELD OR WILDCAT NAME PxA Empire South Deep Unit	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 30-17-29	
12. COUNTY OR PARISH Eddy	13. STATE NM
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3637 GL	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 8-31-81. Ran retrievable bridge plug and set at 7810' and capped with 35' of cement. Ran tubing and tagged cement at 7775'. Circulated casing with 250 barrels of 10# gelled brine water. Cut 5-1/2 casing at 2890' and pulled casing. Spotted 50 sacks of class C cement from 2944'-2730'. Tagged cement at 2730. Spotted 35 sacks class C cement from 375'-475'. Spotted 35 sacks class C cement from 100' to surface. Erected PxA marker. Moved out service unit 9-4-81.

Post ID-2
11-5-82
P419

0+6-USGS,R 1-HOU 1-DMF 1-W. STAFFORD, HOU

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark L. Freeman TITLE Ast. Adm. Analyst DATE 7-7-82

APPROVED

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL IF ANY:

NOV 2 1982

FOR
JAMES A. GILLHAM
DISTRICT SUPERVISOR* See Instructions on Reverse Side

RECEIVED
JUL 13 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
TOSWELL, NEW MEXICO