

IT IS THEREFORE ORDERED:

WFX 467 8-18-28

That the applicant, Windfohr Oil Company, be and the same is hereby authorized to inject water into the San Andres formation through plastic-lined tubing set in packers at approximately 3250 feet in the following described wells for purposes of secondary recovery, to wit:

Grayburg-Jackson Unit Well No. 45 located in Unit B of Section 13, and Grayburg-Jackson Unit Well No. 46 located in Unit B of Section 12, both in Township 17 South, Range 30 East, NMPM, Eddy County, New Mexico.

IT IS FURTHER ORDERED:

That the operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That the injection well or system shall be equipped with a pop-off valve or device which will limit the well-head pressure to a maximum of 1640 pounds per square inch.

That the operator shall notify the supervisor of the Division's Artesia District Office before injection is commenced through said well;

That the operator shall immediately notify the Supervisor of the Division's Artesia District Office of the failure of the tubing, casing, or packer in said well or the leakage of water from or around said well and shall take such steps as may be timely or necessary to correct such failure or leakage.