

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
OCT 27 11 45 AM '88

2. NAME OF OPERATOR
Hondo Oil & Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 2208, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1980' FNL & 660' FEL

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3896' GL

5. LEASE DESIGNATION AND SERIAL NO.

LC-029426-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H. E. West "B"

9. WELL NO.

36

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9-T17S-R31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/15-16/88 Spudded well @ 11:00 a.m. 10/15/88. Drilled 12 1/4" hole to 541'.
Ran 13 jts. of 8 5/8" 24# casing and set @ 541'. Cemented with
400 sx. Premium Plus w/2% CC + 1/4 lb./sx. FloCele. Circulated
100 sx. WOC 9 hrs. Plug down @ 9:30 p.m. 10/16/88. Tested BOP
and casing to 500 psi - held okay. Drilled out with 7 7/8" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ron Brown

TITLE Engineer

DATE 10/25/88

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

NOV 8 1988

*See Instructions on Reverse Side

SJS

CARLSBAD, N.M.