Form 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

## UN TED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

IM OIL CONS COMMISSION

Drawer DD

Artesia, NM FORM APPROVED

Date

Budget Bureau No. 1004-0135 Expires March 31, 1993 SUNDRY NOTICES AND REPORTS ON WELLS 5. Lease Designation and Scrial No. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC 029435-B Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas Mell Mell □ 0#\*\* 8. Well Name and No. 2. Name of Operator **DÉVON ENERGY OPERATING CORPORATION** J. L. Keel "B" #59 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1600, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530 30-015- 27 VI 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 1280' FNL & 1000' FWL, Sec. 6-T17S-R31E Grayburg Jackson 11. County or Parish, State Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud & set surface csg Dispose Water (Note: Report results of multis Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Spud well @ 7:45 p.m., 12/15/94. Ran 8 5/8" csg as follows: Guide shoe @ 438' 2 jts 8 5/8", 24 ppf, J-55, 8rd ST&C csg Float collar @352' 8 jts 8 5/8", 24 ppf, J-55, 8rd ST&C csg Cmt'd csg as follows: 215 sx 35/65 Poz C + 6% D-20 + 2% S-1 + 1/4 lb/sk D-20 + 10% D-42 (Slurry weight = 12.5 lb/gal Slurry yield = 1.94 cft/sx) 200 sxs Class "C" + 2% S-1. (Slurry weight = 14.8 lbs/gal Slurry yield = 1.32 cft/sk) Circ'd 116 sx to surface. 14. I hereby certify that the foregoing is true and correct KAREN ROSA ENGINEERING TECHNICIAN Title Date 12/20/94 (This space for Federal or State office use

Title