

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-2135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals.

5. Lease Designation and Serial No.
LC-029420-B
6. If Indian, Allotee or Tribe Name

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

The Wiser Oil Company

3. Address and Telephone No.

207 W. McKay, Carlsbad, NM 88220 885-5433

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1240' FSL & 1190' FEL, Unit P, Section 21 T17S, R31E

7. If Unit or CA Agreement Designation

Skelly Unit

8. Well Name and No.

Skelly Unit No. 248

9. Well API No.

30-015-

10. Field and Pool, or Exploratory Area

Grayburg Jackson 7RVS QN BG SA

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other - Additional Information
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

For APD

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)

The following information should be attached to the Application for Permit to Drill the above referenced well:

Mud Weight & Characteristics:

0' - 550' Fresh Water Wt. = 8.3 ppg
550' - TD Brine Water Wt. = 9.5 - 10.5 ppg

Viscosity = 30
Viscosity = 28

Casing & Cement

8 5/8" 8RD ST&C 24# J-55 new csg
5 1/2" 8RD LT&C 17# J-55 new csg

Cmt w/ 300 sx Class "C" cmt w/ 2% CaCl. Circ to surface.
Cmt w/ 700 sx Halliburton Lite w/ 1/4# Flocele, 325 sx Premium Plus w/ .5% Halad-9 & 325 sx Premium Plus w/ .5% Halad-344 w/ 3% KCl.

Estimated Maximum Bottom Hole Pressure: 1980 psi

Duration of Program: Drilling - Nine (9) days
Completion - Thirty (30) days

BOP Working Pressure: 3000 psi

14. I hereby certify that the foregoing is true and correct


Signed

Melanie Parker

Title

Agent

Date



(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved By

Title

Date

Conditions of approval, if any:

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side