

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

C/SF
Op.

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II


P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Paseo St.
Santa Fe, NM 87505



WELL API NO.

30-015-29985

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER ☒ Dry & Abandoned

2. Name of Operator

Enron Oil & Gas Company

3. Address of Operator

P.O. Box 2267 Midland, TX 79702

4. Well Location

Unit Letter G : 1700 Feet From The North Line and 1900 Feet From The East Line

Section 36 Township 17S Range 29E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3564' (GL)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08/27/98-TD @ 11400'.

02/28/98- Logged well with ZDL/CN/GR/MAC/STAR/DSL/DIFL.

03/01/98-1st Plug:170sx, Class "H" from 10478' top 10226'-252'; 15.6 ppg, 1.18 cu ft/sx.

2nd Plug:70sx, Class "H" from 7938' to 7838'-100'; 15.6 ppg, 1.18 cu ft/sx.

3rd Plug:70sx, Class "H" from 5838' to 5738'-100'; 15.6 ppg, 1.18 cu ft/sx.

4th Plug:50sx, Class "H" from 4021' to 3881'-140'; 15.6 ppg, 1.18 cu ft/sx.

WOC for 2-3/4 hours and tagged cement plug at 3881'.

5th Plug:35sx, Class "H" + 3% CaCl from 725' to 625'-100'; 15.6 ppg, 1.18 cu ft/sx.

6th Plug:35sx, Class "H" + CaCl from 100' to surface-100'; 15.6 ppg, 1.18 cu ft/sx.

03/02/98-ND BOP. Cut-off casing heads. Install dry hole marker and restore location.

Post ID-2
10-29-99
P+H

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Mike Francis

TITLE Agent

DATE 09/13/99

TYPE OR PRINT NAME Mike Francis

TELEPHONE NO. 915/686-3600

(This space for State Use)

APPROVED BY

Phil Hawkins

TITLE

Field Rep. I

DATE 11-23-99

CONDITIONS OF APPROVAL, IF ANY: