

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY
P.O. BOX 2088
SANTA FE, NEW MEXICO 87501
FEB 18 1986
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-73

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator H & S OIL COMPANY	8. Farm or Lease Name Nix & Curtis
3. Address of Operator Suite 303, First National Bank Bldg., Artesia NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER E, 1980 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 25 TOWNSHIP 18S RANGE 26E NMPM.	10. Field and Pool, or Wildcat Dayton, Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3290 GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER Test for Salt Water Disposal Well <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to test the Nix & Curtis #1 well for a Salt Water Disposal Well and the Lower Yeso Sand, from 3550' - 3900'.
We plan to set cement plug at 6252', open hole up through bottom of 4" liner at 6152'.
Set another 100 foot cement plug at 5323' - 5223' at the top of 4" flush joint liner.
Set bridge plug with cement dumped by bailer at 4900'. This will be 50' below the top of cement on outside of 5 1/2" production string, perforate at 4000', Cement back and into surface pipe with 480 sacks. Wait on cement.
Perforate 50' above bottom of sand zone at 3850' back to 3590' (260 ft)
We will determine at this time if stimulation is needed.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Herbert R. Spencer TITLE Partner DATE 2-18-86

APPROVED BY Les A. Clements TITLE Supervisor District 11 DATE FEB 21 1986

CONDITIONS OF APPROVAL, IF ANY: