

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>C. E. Baker & N. Muncy Jr.</i>		Lease <i>crozier</i>		Well # <i>1</i>	
Location of Well	Unit <i>980N 2362 W</i>	Section <i>26</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor	<i>W. J. J. J.</i>		Type of Equipment		

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>old csg. 10"</i>	<i>8"</i>	<i>32</i>		<i>878</i>	<i>205</i>
* <i>New 7 7/8"</i>	<i>5 1/2"</i>	<i>15.5</i>		<i>1850</i>	<i>225 cu.</i>

Casing Data:

Surface *65* joints of *5 1/2* inch *13.5* # Grade *J-55 API used*
(Approved) (Rejected)

Inspected by *Selma Mermis* date *8-17-76*

Cementing Program

Size of hole *7 7/8* Size of Casing *5 1/2* Sacks cement required *600/cy*
Type of Shoe used *Guide* Float collar used *Insc. T Btm* # jts *welded* *Thread Lock*
TD of hole *1899'* Set *1893'* Feet of *5 1/2* Inch *15.5* # Grade *J-55*
New-used csg. @ *1893'* with *600/* sacks neat cement around shoe *Class C Neat*
+ *sax* additives

Plug down @ *5:30* (AM) (PM) Date *8-17-76*

Cement circulated *Yes* No. of Sacks *100/cy*

Cemented by *Dowell* Witnessed by *Selma Mermis*

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: