

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>KALLARD PET. CO</u>		Lease <u>MAYER- HOLT</u>		Well # <u>1</u>	
Location of Well	Unit <u>L</u>	Section <u>28</u>	Township <u>18^s</u>	Range <u>26^E</u>	County <u>EDDY</u>
Drilling Contractor	<u>LEE DRILLING CO</u>		Type of Equipment <u>ROTARY</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11</u>	<u>8 5/8</u>	<u>2.4</u>	<u>NEW</u>	<u>1200</u>	<u>475</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>11.60</u>	<u>NEW</u>	<u>9300</u>	<u>750</u>

Casing Data:

Surface 51 joints of 2 7/8 inch 24 # Grade J.S. API
(Approved) (Rejected) NEW PIPE

Inspected by LOBLEY date 7-27-61

Cementing Program

Size of hole 11 Size of Casing 8 5/8 Sacks cement required 290

Type of Shoe used PIPE Float collar used YES Btm 3 jts welded THRED-LOCK

TD of hole 1275 Set 1256 Feet of 8 5/8 Inch 24 # Grade J.S. API

New ~~used~~ csg. @ 100 with 100 sacks neat cement around shoe

+ 1120 sack 1120 additives 290 GEL + 290 Calcium Chloride

Plug down @ 105 (AM) (PM) Date 7-28-61

Cement circulated YES No. of Sacks 5

Cemented by TALLIBORIAN Witnessed by LOBLEY

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by LOBLEY

Remarks:

1256
12311

1256

1256

1256

375