

|  |  |  |
|--|--|--|
|  |  |  |
|  |  |  |
|  |  |  |

County Edwy Depth 6135' Pool Empire Abo Undesig.\*

SCOUT REPORT  
NEW MEXICO OIL CONSERVATION COMMISSION

Company Pan American Pet Corp. Well No. 1 Lease State AT

1880 Feet from S Line 660 Feet from W Line, Sec. 2 Twp. 18S Rge 27E

|           |             |                                    |                                                  |
|-----------|-------------|------------------------------------|--------------------------------------------------|
| S/B       |             | Land State                         | Contractor <u>Lee Drlg. Co.</u>                  |
| T. A      |             | Elevation <u>3544<sup>DF</sup></u> | Spudded <u>10-9-58</u> Completed <u>11-22-58</u> |
| T. X      |             |                                    |                                                  |
| B. X      |             |                                    |                                                  |
| T. Del Li |             | T. Tu                              | Total Depth <u>6094</u> P. B. <u>6038</u>        |
| T. Del Sd |             | T. Full                            | Top Pay <u>5360</u> District <u>9</u>            |
| T. Y      |             | T. DR                              | I.P. <u>F 75</u> BOFD                            |
| T. SR     |             | T. Wich A.                         | Base on <u>BO 24</u> Hrs.                        |
| T. Q      | <u>900</u>  | T. Abony                           | Choke: <u>3/64</u> Inch                          |
| T. PR     |             | T. WC                              | Tubing @ <u>490</u> Csg. Ft.                     |
| T. GB     |             | T. Hu                              | Press: Tbg. <u>490</u> Csg.                      |
| T. SA     | <u>1666</u> | T. Per-Pe                          | GOR <u>1065</u> Gravity <u>42</u>                |
| T. Glo    | <u>3100</u> | T. Penn                            | Effective Perfs.:                                |
| T. Blby   |             | T. Strawn                          |                                                  |
| T. CF     |             | T. Miss                            | <u>1044 5360-86</u>                              |
|           |             | T. WF                              |                                                  |

CSG. & CEMENTING RECORD

| Size         | Feet        | Sax Cement |
|--------------|-------------|------------|
| <u>8 5/8</u> | <u>793</u>  | <u>700</u> |
| <u>5 1/2</u> | <u>6094</u> | <u>200</u> |
|              |             |            |
|              |             |            |
|              |             |            |
|              |             |            |
|              |             |            |

|         |                                |              |
|---------|--------------------------------|--------------|
| T. Dev  | Acid, Frac & Shooting Record:  |              |
| T. Sil  | From                           | To           |
| T. Fuss | <u>500 7A</u> From <u>5360</u> | To <u>86</u> |
| T. Mon  | From                           | To           |
| T. Simp | From                           | To           |
| T. McK  |                                |              |
| T. Ell  |                                |              |
| T. G.W. |                                |              |
| T. Gr   | SHOWS                          |              |
| T.      | S/                             |              |
| T.      | S/                             |              |
| T.      | S/                             |              |
| T.      | S/                             |              |
| T.      | S/                             |              |
| T.      | S/                             |              |

|          |            |                    |   |                                      |
|----------|------------|--------------------|---|--------------------------------------|
| 10-15-58 | <u>Lee</u> | <u>2 11/16 L.</u>  | C | <u>5493-5500</u> sec <u>10</u> hole  |
|          |            | <u>3 11/16 L.</u>  | C | <u>5500-5510</u> sec <u>20</u> hole  |
|          |            | <u>4 11/16 L.</u>  | C | <u>5510-5520</u> sec <u>30</u> hole  |
|          |            | <u>5 11/16 L.</u>  | C | <u>5520-5530</u> sec <u>40</u> hole  |
|          |            | <u>6 11/16 L.</u>  | C | <u>5530-5540</u> sec <u>50</u> hole  |
|          |            | <u>7 11/16 L.</u>  | C | <u>5540-5550</u> sec <u>60</u> hole  |
|          |            | <u>8 11/16 L.</u>  | C | <u>5550-5560</u> sec <u>70</u> hole  |
|          |            | <u>9 11/16 L.</u>  | C | <u>5560-5570</u> sec <u>80</u> hole  |
|          |            | <u>10 11/16 L.</u> | C | <u>5570-5580</u> sec <u>90</u> hole  |
|          |            | <u>11 11/16 L.</u> | C | <u>5580-5590</u> sec <u>100</u> hole |

from

ID 6094 Solo ring csq

C 5673-87 uc 14' Lolo

C 5687-5713 m 25' dolo

C 5713-40 rec 27' solo

C 5740-88 rec 48' solo

C 5788-5838 m 50' 2660

|   |          |    |     |       |
|---|----------|----|-----|-------|
| C | 5837- 88 | in | 50' | Isolo |
|---|----------|----|-----|-------|

|   |           |    |     |      |
|---|-----------|----|-----|------|
| C | 5882-5938 | mc | 50' | Solo |
|---|-----------|----|-----|------|

|   |                                 |
|---|---------------------------------|
| 5 | <del>11</del> 6094 solo PC 6038 |
|---|---------------------------------|

Ref 1044 5360-86

A 500 mA