

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

SUBMIT THIS NOTICE IN TRIPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORK SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE SENDER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLAN SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

INDICATE NATURE OF NOTICE BY CHECKING BELOW

| | | | | | |
|--------------------------------------|---|---|---|--------------------------------------|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | X | NOTICE OF INTENTION TO SHOOT (NITRO) | |
| NOTICE OF INTENTION TO GUN PERFORATE | X | NOTICE OF INTENTION (OTHER) | | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(PLACE)

April 23, 1963
(DATE)

GENTLEMEN:

FOLLOWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW AT THE
Humble Oil & Refining Company Abo Chalk Bluff Draw Unit WELL NO. 15 IN K
(COMPANY OR OPERATOR) (UNIT)
NE 1/4 SW 1/4 OF SEC. 16, T. 18-S, R. 27-E, NMPM., Empire Abo POOL
(40-ACRE SUBDIVISION)
Eddy COUNTY.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Perforate 5261, 5265, 5277, 5282, 5295, 5547, 5553, 5573, 5578, 5583, 5599, 5614, 5628, 5660, 5677, 5691, 5696, 5711, 5724, and 5733' with one jet shot each.
2. Set retrievable bridge plug at 5750' and packer at 5525'. Acidize with 20,000 gallons low fluid loss acid using ball sealers and pinpoint technique.
3. Release packer and retrieve bridge plug. Set bridge plug at 5325' and packer at 5250'. Acidize with 7,500 gallons low fluid loss acid using ball sealers and pinpoint technique.
4. Release packer and retrieve bridge plug.
5. Return well to production.

RECEIVED
APR 25 1963
O. C. O.
ARTESIA, OFFICE

APPROVED APR 25 1963, 19
EXCEPT AS FOLLOWS:

Humble Oil & Refining Company
COMPANY OR OPERATOR
BY [Signature]
POSITION Agent
SEND COMMUNICATIONS REGARDING WELL TO:

APPROVED
OIL CONSERVATION COMMISSION
BY [Signature]

NAME Humble Oil & Refining Company
Hobbs, New Mexico

