


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No.

Unit



RECEIVED
MAR 21 1957

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF	☐
NOTICE OF INTENTION TO CHANGE PLANS	☐	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	☐
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	☐	SUBSEQUENT REPORT OF ALTERING CASING	☐
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	☐	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	☐
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	☐	SUBSEQUENT REPORT OF ABANDONMENT	☐
NOTICE OF INTENTION TO PULL OR ALTER CASING	☐	SUPPLEMENTARY WELL HISTORY	☐
NOTICE OF INTENTION TO ABANDON WELL	☐		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 2

19 57

Well No. 12 is located 990 ft. from (N) line and 330 ft. from (E) line of sec. 6

5.6--4.4--2.2. Sec. 6 18 E 30 A NA NA
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Loco Hills NA NA
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3548 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

well
Plan to drill this to approx. 2800' or to sufficient depth to test the Loco Hills sand. Plan to run and cement approx. 450' of 8 5/8" 24 # surface pipe and approx. 2800' of 7" 20# oil string of casing. Plan to diamond core the Loco Hills section. Plan to gun perforate the 14 oil string into the Loco Hills section and Hydrofrac same with 10,000 gal. oil and 15,000 sand.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Franklin Eaton & Co.

Address Box 218 Loco Hills N.M.

By O.C. Rogers

Title Gen'l. Mgr't.

