

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 27276

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL  GAS WELL  OTHER  DEC 6 - 1979

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR  
H & S Oil Company

O. C. C.

8. FARM OR LEASE NAME

McClay

3. ADDRESS OF OPERATOR  
216 American Home Bldg. - Artesia, New Mexico 88210

ARTESIA, OFFICE

9. WELL NO.

11

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)  
At surface

10. FIELD AND POOL, OR WILDCAT

Benson Queen North

2260' FSL & 1730' FWL Section 33-T18S-R30E

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33-T18S-R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 3468

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Encountered water at 150'

9/30/79 Ran 660' of 8 5/8" 24# casing & cemented W/325 sx. Class C + 75 sx. Cal. Ch.  
10/1/79 Cemented 1" pipe outside of 8 5/8" W/550 sx. Class C + 22 sx. Cal. Ch.

Got water shut-off

10/11/79 Ran 3460' of 5 1/2" 14# casing - 2 stage cement job - Stage 1, 2069' 325 sx cement 50-50 pos. 2% Cal. Ch. 1/4 lb. Cello flakes - Stage 2, (after 6 hr. shut down) 875 sx. 50-50 lite. Cement circulated.

11/2/79 Perforated 2832' to 2861' w/11 holes - 3172' to 3245' w/11 holes - 3388' to 3391' w/8 holes.

11/6/79 Fracture treatment via 2 3/8" tubing @ 20.0-25.0 BPM to 4500-5000 PSI W/95,000 gals. gelled water, 3640# J338 REDIFFRAC service, 95 gal. surfactant, 30,000# FLA 100, 68,500# 20-40 sand, 15,000# 10-20 sand, 1750 gals. acid.

18. I hereby certify that the foregoing is true and correct

SIGNED

*R. L. Heinisch*

TITLE

Partner

DATE

12/4/79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: