

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.T.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

APR 20 1981

O. C. D.

50. Indicate Type of Lease  
State  Fee

51. State Oil & Gas Lease No.  
State 647

SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA OFFICE  
DO NOT USE THIS AREA FOR PROPOSALS TO DRILL OR REFRAC TO A DIFFERENT RESERVOIR.  
USE APPLICATION AND PERMIT FOR SUCH PURPOSES.

OIL WELL  GAS WELL  OTHER Dry

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 S. 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM

THE West LINE SECTION 30 TOWNSHIP 18S RANGE 28E

15. Elevation (show whether DF, RT, GR, etc.)

3558 KB

7. Unit Agreement Name

8. Farm or Lease Name

Illinois Camp NN State

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK   
TEMPORARILY ABANDON   
PULL OR ALTER CASING

PLUG AND ABANDON   
CHANGE PLANS

REMEDIAL WORK   
COMMENCE DRILLING OPNS.   
CASING TEST AND CEMENT JOB

ALTERING CASING   
PLUG AND ABANDONMENT

OTHER

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has been tested in the Morrow, Atoka, Strawn and Canyon, all non-commercial, and we propose to cut off and pull the 4 1/2" casing, plug and abandon the well. Location will be cleaned and marker installed.

FORMATION TOPS	PERFORATIONS	PLUGS
Morrow @10280	10350 - 10414	ClBP @10192' with 30' cmt, PBSD 10162
Atoka @9796	9987 - 10153	ClBP @9600' with 35' cmt, PBSD 9565
Strawn @9110	9193 - 9200	ClBP @9000' with 35' cmt, PBSD 8965
L. Canyon @8506	8882 - 8902	Retainer @ 8850, sqd with 125sx
	8798 - 8802	Retainer @8700, sqd with 125sx
	8582 - 8622	Will set ClBP @8300' with 35' cmt.

Will attempt to recover 7800' of casing. Will spot 35sx across cut off stub. Bone Spring ls @3290, San Andres @2136. Propose to spot 35sx cement plugs at 5500 - 5400, 3350 - 3250 and 2100 - 2000' (8 5/8 casing @ 2050'), 10sx @ surface. + mud between all plugs  
\*15 SX

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Engineer DATE 4-20-81

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE MAY 07 1981

CONDITIONS OF APPROVAL, IF ANY: \* As Noted Above.